

## Declaration of Performance



weber.kol XL Flex  
CPR.3129022

Unique identification code of product-type: weber.kol XL Flex

Type, batch or serial number or any other element allowing identification of the construction product :

weber.kol XL Flex, C2TES1 sınıfı.

Batch and serial number is printing on packaging.

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer :

Polymer-additive, very flexible tile adhesive mortar with reduced slip, extended open time and improved with additional qualities. Used for fixing granite ceramic and glazed porcelain on exterior and interior walls and floors.

Name, registered trade name or registered trade mark and contact address of manufacturer :

Saint-Gobain Weber Yapı Kimyasalları San ve Tic. A.Ş  
Ansızca Köyü, Ansızca İç Kısım San. Sokak No: 284 35171  
Kemalpaşa/İzmir –TÜRKİYE

System or systems of assesment and verification of constancy of performance of the construction product :

Sistem 3

Identification number of tests approved by accredited laboratories: 1783/2164

### Declared performance

Essential characteristic	Performance	Harmonised technical specification
Yangına tepki sınıfı	A1	EN 12004
Initial tensile adhesion strength	$\geq 1 \text{ N/mm}^2$	
Tensile adhesion strength after heat ageing	$\geq 1 \text{ N/mm}^2$	
Tensile adhesion strength after water immersion	$\geq 1 \text{ N/mm}^2$	
Tensile adhesion strength after freeze-thraw	$\geq 1 \text{ N/mm}^2$	
Open time by tensile adhesion	At least 30 min. after $\geq 0,5 \text{ N/mm}^2$	
Transverse deformation	$5 \text{ mm} > S1 \geq 2,5 \text{ mm}$	
Slip resistance	$\leq 0,5 \text{ mm}$	

The performance of the product identified in point 1 and 2 is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by :

  
Ashi Çelik  
R&D and Quality Control Director  
TR/ 20.03.15