

weber.art tavan

Interior ceiling paint

Technical Data Sheet
Issued on: 20.05.2019
Revision No: 001

■ Description

Acrylic,based, interior ceiling paint

■ Reference standards

- TS 5808
- G marking
- Public Works Pos No: 04.524/01

■ Advantages

- Provides easy application with its high covering feature
- Can be wiped
- Allows substrate to breathe
- Odorless
- High adherence and covering decorative purposes.

■ Range of application

Used on ceilings of interiors of all buildings for decorative purposes.

■ Application substrates

- Interior walls;
- Cement-based renders,
- Concrete (**weber.tec R**, **weber.tec RK** or **weber.tec RM** applied),
- Plaster render, gypsum block, plaster board substrates,
- Gas concrete (gas concrete render or **weber.tec RM** applied),
- Old painted substrates,
- Please consult us for all other application substrates

■ Preparation of substrates

- Substrate should be clean, dry, smooth and sound. • Substrates should be primed with **weber.prim art**
- without diluting and application of **weber.art tavan** should be started at least 6 hours later

■ Conditions of application

- Ambient temperature is between: +5 °C and +30 °C. • Avoid application in very damp and/or hot weather.

■ Application

- **weber.art tavan** should be diluted with water in the rate of 30 % for the first and second coat in brush and roller application, and should be mixed well until homogenous state is achieved.
- **weber.art tavan** should be applied to the entire substrate in two coats with lambskin roller or brush roller.
- Wait for minimum 2 hours between coats.

■ Application tools

Lambskin roller, brush

■ Consumption

350 gr/m² (for two layers)

■ Teknik bilgiler

PRODUCT	weber.art tavan
Product type	Liquid
Application temperature	+5°C ile +30°C arası
Color	White
Density	~ 1,24 gr/cm ³
PERFORMANCE	
Wet scrub resistance	Class 5
Covering	Class 1 (4,5 m ² /l)
Grain size	Thin
Glossiness	Semi matt

■ Points of attention

- To avoid tonality differences, products which have the same BATCH NUMBER and PRODUCTION DATE should be used on each facade.
- Never use saltwater, lime or any other foreign substances.
- All equipment used should be washed right after the application before drying with clean water.
- Paint and solution should be mixed as the amount planned to be used.

■ Storage

Packaging	<ul style="list-style-type: none">• 17,5 kg• 10 kg• 3,5 kg
Shelf life	<ul style="list-style-type: none">• A year from date of manufacture when stored unopened in a dry, moisture-free environment. Packages should be kept tightly closed when not in use.• Packages should be protected against frost.

* The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

* Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş. is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş.
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284 • 35730 Kemalpaşa • İzmir • Türkiye
Tel: +90 (232) 397 07 00 • www.tr.weber • info@weber.com.tr • Çözüm Hattı 444 6 990



■ Safety precautions

- Use the appropriate safety equipments (gloves, goggles).
- Protect your eyes / face.
- Avoid contact with eye and skin.
- In case of contact with eyes, rinse immediately with plenty of water and consult a specialist.
- Read the material safety data sheet for more detailed safety information.

Legal Warning

Saint-Gobain Weber Yapı Kimyasalları San. Ve Tic. A.Ş. is not responsible for any errors arising from the use of product beyond its intended purpose or not complying the application procedures mentioned above.

* The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

* Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş. is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş.

Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284 • 35730 Kemalpaşa • İzmir • Türkiye
Tel: +90 (232) 397 07 00 • www.tr.weber • info@weber.com.tr • Çözüm Hattı 444 6 990

