

weber.prim art

Satin primer

Technical Data Sheet

Issued on: 27.06.2019

Revision No: 002

■ Description

Satin primer.

■ Range of application

- Used as a primer under the synthetic and waterbased paints in interiorwalls of surfaces especially on highabsorbing and high-porosity substrates to increase adherence and reduce final coat paint consumption.
- Before tile fixing applications; used as a primer on high-absorbing surfaces to provide water and damp impermeability and to increase adherence.
- It is applied as transition primer, especially if ceramic applications will be made on gypsum surfaces.

■ Application substrates

- Interior walls;
- Cement-based renders,
- Concrete (**weber.tec R**, **weber.tec RK** or **weber.tec RM** applied),
- Plaster render, gypsum block, plaster board substrates,
- Gas concrete (gas concrete render or **weber.tec RM** applied),
- Old painted substrates,
- Please consult us for all other application substrates.

■ Conditions of application

- Ambient temperature is between +5 °C and +30 °C
- Avoid application in very damp and/or hot weather

■ Application

- **weber.prim art** should be mixed without diluting until homogeneous and shoul be applied as a single coat with a lambskin roller or brush.
- Paint application should be started at least 6 hours after the application of **weber.prim art**.
- Waterproofing or tile fixing application should be started at least 6 hours after **weber.prim art** application.

■ Application tools

Lambskin roller and brush.

■ Consumption

12 m²/l

■ Technical details

PRODUCT	weber.prim art
Product type	Liquid
Application temperature	Between +5°C and +30°C
Drying time	6-24 hour
Color	Transparent

■ Points of attention

- Not applicable on wet and damp substrates.
- Not applicable on wooden and metal substrates.
- Not applicable on wall paper directly.
- Not applicable on tile over tile fixing applications.
- All tools used for application should be cleaned with water before drying.

■ Storage

Packaging	<ul style="list-style-type: none">• 15 l• 1 l
Shelf life	<ul style="list-style-type: none">• A year from date of manufacture when stored unopened in a dry, moisture-free environment. Packages should be kept tightly closed when not in use.• Packages should be protected against frost.

■ Safety precautions

- Use the appropriate safet equipments (gloves, goggles).
- Protect your eyes / face.
- Avoid contact with eye and skin.
- In case of contact with eyes, rinse immediately with plenty of water and consult a specialist.
- Read the material safety data sheet for more detailed safety information.

Legal Warning

Saint-Gobain Weber Yapı Kimyasalları San. Ve Tic. A.Ş. is not responsible for any errors arising from the use of product beyond its intended purpose or not complying the application procedures mentioned above.

hestatedtimesapplyfor20°Csubstrateandambienttemperatureandincreaseatlowertemperaturesanddecreaseathightemperatures.

** Saint-GobainWeberYapıKim.San.veTic.A.Ş.isnotresponsiblefortheapplicationerrorsarisingfromuseofproductbeyonditsintendedpurposeor failure to comply with the foregoing application conditions and advice on the product.*



Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş.
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284 • 35730 Kemalpaşa • İzmir • Türkiye
Tel: +90 (232) 397 07 00 • www.tr.weber • info@weber.com.tr • Çözüm Hattı 444 6 990

