

weber.tex MULTICOLOR

Silicone added façade paint

Technical Data Sheet
Issued on: 06.11.2020
Revision No: 005

■ Description

Acrylic emulsion-based, silicone added, matt façade paint.

■ Reference standards

- TS 7847
- G marking
- Public Works Pos No: 10.300.1009

■ Advantages

- High covering power and adherence.
- Water repellent.
- Highly vapor permeable.
- Resistant to external factors.
- Retains the appearance as new for a long time.

■ Range of application

Applied as a final paint on façade of all buildings.



■ Application substrates

- Exterior walls;
- Cement based renders,
 - Concrete (**weber.tec R**, **weber.tec RK**, **weber.tec RM** or **weber.tex organic paste** applied),
 - Gas concrete (gas concrete render applied),
 - Please consult us for all other application substrates

■ Preparation of substrate

- The substrate should be clean, dry, smooth and sound.
- The substrate should be primed with single coat **weber.prim C 100** diluted in the ratio of 5/1 (**weber.prim C 100**/water) and application of **weber.tex MULTICOLOR** should be started after at least 12 hours.
- The substrates on which **weber.tec RM** has been applied should be primed as single layer with **weber.prim art** without diluting and the entire substrate should be primed with **weber.prim C 100** diluted in the ratio of 5/1 (**weber.prim C 100**/water) as single layer after drying (min. after 6 hours) and application of **weber.tex MULTICOLOR** should be started at least 12 hours later.
- For a better result, **weber.prim C 100** fit for the color of **weber.tex MULTICOLOR** to be applied should be chosen.

■ Conditions of application

- Ambient temperature: between +5 °C and +30 °C
- Avoid application in very damp and/or hot weather, in strong wind or under sunlight.
- It should not be used on substrates which are frozen or melting or have the risk of frost or rain within 24 hours.
- Not applicable on horizontal and inclined substrates with an angle less than 45 degrees.

■ Application tools

Lambskin roller and brush.

■ Application

- In brush or roller application, **weber.tex MULTICOLOR** diluted in the ratio of 10/1 (**weber.tex MULTICOLOR** / water) for the first and second layer should be mixed until it reaches a homogenous state.
- **weber.tex MULTICOLOR** should be applied on the whole substrate as 2 layers with lambskin roller or brush.
- Wait for at least 2 hours between layers.

■ Consumption

4-5 m²/l (for two coats)

* The consumption amounts given are average values. The amount of consumption may vary depending on the weather conditions of the application, the application surface and the absorbency of the surface, and the type of roller used.

■ Technical specifications

PRODUCT	weber.tex MULTICOLOR
Chemical structure	Liquid
Application temperature	between +5°C and +30°C
Drying time	6-24 hours
Colour	400 Colour
Density	~1,55 gr/cm ³
PERFORMANCE	
Glossiness	G3
Dry film thickness	E2
Grain size	S1
Vapor transmission rate	V1
Water transfer rate	W3
Crack bridging capability	A0
CO ₂ permeability	C0

The stated times apply for 20°C substrate and ambient temperature; increase at lower temperatures and decrease at higher temperatures.

Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş. is not responsible for the application errors arising from use of product beyond its intended purpose of failure to comply with the forgoing application conditions and advice on the product.



Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş.
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284 • 35730 Kemalpaşa • İzmir • Türkiye
Tel: +90 (232) 397 07 00 • www.tr.weber • info@weber.com.tr • Çözüm Hattı 444 6 990



■ Attention points

- To avoid tonality differences, the products which have the same BATCH NUMBER and PRODUCTION DATE should be used at each façade.
- Never use salty water, lime and similar foreign substances.
- All tools used for application should be cleaned with water before drying.

■ Storage

Packaging	<ul style="list-style-type: none">• 15 l buckets• 7,5 l buckets
Shelf life	<ul style="list-style-type: none">• 1 year from the production date in dry and cool ambient.• Package should be kept tightly closed when not in use. Package should be protected against frost.

■ Safety precautions

- Use the appropriate safety equipment (dust mask, gloves).
- Protect your Eyes / face.
- Avoid contact with eyes and skin.
- In case of contact with eyes, rinse immediately with plenty of water and consult a specialist.
- Read the Material Safety Data Sheet for more detailed safety information.

Legal warning

Since there are different conditions and requirements that apply in any case, Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş. can not be liable for other than the information provided in this product datasheet. The information provided in this product data sheet is based on our current knowledge and experience about the product. All of the above information must be considered as guidelines. It is the user's responsibility to ensure that the product is suitable for the intended use, and also to perform acceptance check and self-inspection control. The user is responsible if the product is used for purposes other than recommended or for improper installation.

The stated times apply for 20°C substrate and ambient temperature; increase at lower temperatures and decrease at higher temperatures.

Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş. is not responsible for the application errors arising from use of product beyond its intended purpose of failure to comply with the forgoing application conditions and advice on the product.



Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş.
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284 • 35730 Kemalpaşa • İzmir • Türkiye
Tel: +90 (232) 397 07 00 • www.tr.weber • info@weber.com.tr • Çözüm Hattı 444 6 990

