

# weber geokeçe

## Waterproofing fleece

Technical Data Sheet  
Issued On: 02.12.2019  
Revision No: 005

### ■ Description

Waterproofing fleece made of non-woven polyester fibers, improves durability of the waterproofing layer.

### ■ Advantages

- Easy and simple application
- Resistant to chemicals
- Long-lasting

### ■ Application areas

Used as reinforcing middle layer for liquid resin based (like electromeric and polyurethane) waterproofing products. Also helps obtaining a homogenous application thickness.

### ■ Application

- Should be applied by laying out on the substrate right after the first coat application of liquid resin based products. Use a brush or trowel to create high-adherence bonding with the waterproofing layer.
- Next coat of waterproofing application should be made on the fleece and cover the whole substrate.

### ■ Storage

Packaging	100 linear meter roll (150 m <sup>2</sup> )
Shelf life	• 2 years from date of manufacture.

### ■ Safety precautions

- Use appropriate safety equipment (mask, gloves, glasses).
- Protect your eyes/face.
- Avoid direct contact with eyes and skin.
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Please read Safety Data Sheet (SDS) for further safety information.

### LEGAL DISCLAIMER

Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş. is not responsible for any errors arising from the use of product beyond its intended purpose or not complying the application procedures mentioned above.

### ■ Technical specifications

PRODUCT	weber geokeçe
Weight	45 g/m
Thickness	0,25 mm
Width	1,5 m
PERFORMANCE	
Tensile strength	≥2,00 kN/mm <sup>2</sup> (TS EN ISO 10819)
Elongation at break	≥%50 (TS EN ISO 10819)

The stated times apply for 20°C substrate and ambient temperature; increase at lower temperatures and decrease at higher temperatures.

Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş. is not responsible for the application errors arising from use of product beyond its intended purpose of failure to comply with the forgoing application conditions and advice on the product.



Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş.  
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284 • 35730 Kemalpaşa • İzmir • Türkiye  
Tel: +90 (232) 397 07 00 • www.tn.weber • info@weber.com.tr • Çözüm Hattı 444 6 990

