

weber köşebant 100/120

Flexible waterproofing tape

Technical Data Sheet
Issued On: 02.12.2019
Revision No: 002

Description

Synthetic rubber based, polyester felt backed waterproofing tape for moving joints, wall and floor corners in wet areas.

Advantages

- High flexibility even at lower temperatures
- Chemical resistance
- Two different size options
- Resistant to tears and heat

Application areas

Used as waterproofing tape resistant to diluted acids, sodium solutions, polar solvents like alcohol and ketone in wet areas like bathrooms, kitchens, toilets and balconies; terraces, industrial kitchens, laboratories and car wash centers; under-tiling waterproofin applications to support water tightness of movable joints, wall and floor corners.

Preparation of substrates

- The substrate should be clen, sound and free from adhesion diminishing residues.

Application

- After the completion of first coat waterproofing application, side sections **weber köşebant** is placed on the application substrate while the waterproofing material is still wet.
- Second coat waterproofing material application should be on the entire surface including sides of **weber corner waterproofing tapes**.
- Ensure that the tension areas of waterproofing tapes (middle sections) do no contact with waterproofing material.

Points of attention

- Not applicable on substrates with the risk of contacting aromatic compounds like mineral oils, benzene, gasoline and toulene.
- Silicone based joint sealants should be applied on tiling joints in projection to protect **weber köşebant** against mechanical impacts.
- Waterproofing tapes should be fixed to each other using the waterproofing material used on the substrate on tape joints or crossings.

Technical specifications

PRODUCT	weber.rep grout
Total width	weber köşebant 100: 10 cm (tensile zone 5 cm) weber köşebant 120: 12 cm (tensile zone 7 cm)
Horizontal bending strengtj	Approx. 190%
Heat resistance	Between -30°C and +90°C
Hardness (Shore A)	50
Pressureized water resistance	2 bars

Storage

Packaging	10 m and 50 m roll
Shelf life	2 years from date of manufacture.

Safety precautions

- Use appropriate safety equipment (mask, gloves, glasses).
- Protect your eyes/face.
- Avoid direct contact with eyes and skin.
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Please read Safety Data Sheet (SDS) for further safety information.

LEGAL DISCLAIMER

Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş. is not responsible for any errors arising from the use of product beyond its intended purpose or not complying the application procedures mentioned above.

The stated times apply for 20°C substrate and ambient temperature; increase at lower temperatures and decrease at higher temperatures.

Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş. is not responsible for the application errors arising from use of product beyond its intended purpose of failure to comply with the forgoing application conditions and advice on the product.



Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş.
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284 • 35730 Kemalpaşa • İzmir • Türkiye
Tel: +90 (232) 397 07 00 • www.tnweber • info@weber.com.tr • Çözüm Hattı 444 6 990



The stated times apply for 20°C substrate and ambient temperature; increase at lower temperatures and decrease at higher temperatures.
Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş. is not responsible for the application errors arising from use of product beyond its intended purpose of failure to comply with the forgoing application conditions and advice on the product.



Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş.
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284 • 35730 Kemalpaşa • İzmir • Türkiye
Tel: +90 (232) 397 07 00 • www.tr.weber • info@weber.com.tr • Çözüm Hattı 444 6 990

