

Revision nr. 1

Dated 08/05/2020

Printed on 08/05/2020

Page n. 1/10

## 6232 – weber.tex beton design

# 6232 – weber.tex beton design Safety data sheet

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 6232

Product name Weber.tex beton design

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Acrylic based, ready-to-use colored plaster that can be applied on interior

and exterior surfaces with concrete appearance.

1.3. Details of the supplier of the safety data sheet

Name Saint-Gobain Weber Yapi Kim. San. ve Tic. A.S. Full address Kemalpaşa O.S.B. Mah Kuyucak Yolu Sok:284

District and Country 35730 Kemalpaşa / İZMİR

TURKEY

Fax 0 232 397 08 00

Tel. 0 232 397 07 00

1.4. Emergency telephone number

For urgent inquiries refer to 0 232 397 07 13-07 84

Ulusal Zehir Danışma Merkezi (UZEM) :114

### SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication:

Skin Sens. 1 H317

2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments. Danger Symbols:

R phrases:

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Revision nr. 1

Dated 08/05/2020

Printed on 08/05/2020

Page n. 2/10

# 6232 – weber.tex beton design



Signal words: Warning

Hazard statements:

H317 May cause an allergic skin reaction.

Precautionary statements:

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves / protective clothing / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P321 Specific treatment (see on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice / attention.

P363 Wash contaminated clothing before reuse.

Contains: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2Hisothiazol-3-one

2.3. Other hazards.

Information not available.

## SECTION 3. Composition/information on ingredients.

INDEX. 613-167-00-5

3.1. Substances.

Information not relevant.

3.2. Mixtures. Note: Upper limit is not included into the

Identification. Conc. %. Classification 67/548/EEC. Classification 1272/2008 (CLP). AMMONIA

Skin Corr. 1B H314, STOT SE 3 H335, Aquatic

CAS. 1336-21-6 0 - 0,5 CR34, N R50, Note B Acute 1 H400 M=1, Note B

EC. 215-647-6

INDEX. 007-001-01-2

Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox.

chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2Hisothiazol-3-one Acute 1 H400 M=1, Aquatic Chronic 1

5-chloro-2-methyl-4-isothiazolin-3-one and 2- methyl-2Hisothiazol-3-one methyl-2Hisothiazol-3-one Acute 1 H400 M=1, Acut

EC. -

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

 $T+= Very\ Toxic(T+),\ T=Toxic(T),\ Xn=Harmful(Xn),\ C=Corrosive(C),\ Xi=Irritant(Xi),\ O=Oxidizing(O),\ E=Explosive(E),\ F+=Extremely\ Flammable(F+),\ F=Highly\ Flammable(F),\ N=Dangerous\ for\ the\ Environment(N)$ 



Revision nr. 1

Dated 08/05/2020

Printed on 08/05/2020

Page n. 3/10

# 6232 – weber.tex beton design

### SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention. SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

### SECTION 5. Firefighting measures.

5.1. Extinguishing media.

#### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.

### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters.

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

#### Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.



Revision nr. 1

Dated 08/05/2020

Printed on 08/05/2020

Page n. 4/10

## 6232 – weber.tex beton design

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

### SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

United Kingdom EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits for use

with the Control of Substances Hazardous to Health Regulations (as amended).

Éire Code of Practice Chemical Agent Regulations 2011.

OEL EU Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.

TLV-ACGIH ACGIH 2012

### AMMONIA

Threshold	Limit	Value

Туре	Country	TWA/8h		STEL/15min	STEL/15min	
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH		17	25	24	35	

#### Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

8.2. Exposure controls.



Revision nr. 1

Dated 08/05/2020

Printed on 08/05/2020

# 6232 – weber.tex beton design

Page n. 5/10

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

### SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance Not available.

Colour Not available.

Odour Not available.

Odour threshold. Not available.

pH. Not available.

Melting point / freezing point. Not available. Initial boiling point. Not

available.

Boiling range. Not available. > 60 °C. Flash point. Not available. **Evaporation Rate** Flammability of solids and gases Not available. Lower inflammability limit. Not available Upper inflammability limit. Not available. Lower explosive limit. Not available. Upper explosive limit. Not available. Vapour pressure. Not available. Vapour density Not available.



Revision nr. 1

Dated 08/05/2020

Printed on 08/05/2020

Page n. 6/10

# 6232 – weber.tex beton design

Relative density. Not available. Not available. Solubility Partition coefficient: n-octanol/water Not available. Auto-ignition temperature. Not available. Decomposition temperature. Not available. Not available. Viscosity Explosive properties Not available. Oxidising properties Not available. 9.2. Other information.

 Solid content.
 62,92 %

 VOC (Directive 1999/13/EC) :
 < 0.01 %</td>

 VOC (volatile carbon) :
 < 0.01 %</td>

## SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

Information not available.

### SECTION 11. Toxicological information.

### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurvies, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurfy skin, dryness, ulcerations and skin thickening prevail during the chronic phase.



Revision nr. 1

Dated 08/05/2020

Printed on 08/05/2020

Page n. 7/10

# 6232 – weber.tex beton design

AMMONIA

LD50 (Oral). 350 mg/kg Rat

### SECTION 12. Ecological information.

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil, sewers and waterways. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity.

#### AMMONIA

LC50 - for Fish.

47 mg/l/96h Channa punctata EC50 - for

Crustacea.

20 mg/l/48h Daphnia magna

12.2. Persistence and degradability.

Information not available.

12.3. Bioaccumulative potential.

Information not available.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

# SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Avoid littering. Do not contaminate soil, sewers and waterways.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### SECTION 14. Transport information.

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

# SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category.

None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006. Product.

Point.

3



Revision nr. 1

Dated 08/05/2020

Printed on 08/05/2020

Page n. 8/10

6232 – weber.tex beton design

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

### SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 3 Acute toxicity, category 3
Skin Corr. 1B Skin corrosion, category 1B

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Skin Sens. 1 Skin sensitization, category 1

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:



Revision nr. 1

Dated 08/05/2020

Printed on 08/05/2020

Page n. 9/10

## 6232 – weber.tex beton design

R23/24/25 TOXIC BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.

R34 CAUSES BURNS.

R43 MAY CAUSE SENSITISATION BY SKIN CONTACT.

R50 VERY TOXIC TO AQUATIC ORGANISMS.

R50/53 VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE

EFFECTS IN THE AQUATIC ENVIRONMENT.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation WGK: Water hazard classes (German).

### GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments
- Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- Regulation (EC) 1272/2008 (CLP) of the European Parliament
- Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- Regulation (EC) 453/2010 of the European Parliament
- Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
- Regulation (EC) 618/2012 (III Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- 10. Handling Chemical Safety
- 11. Niosh Registry of Toxic Effects of Chemical Substances
- 12. INRS Fiche Toxicologique (toxicological sheet)
- 13. Patty Industrial Hygiene and Toxicology
- 14. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition 15. ECHA website Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property.



Revision nr. 1

Dated 08/05/2020

Printed on 08/05/2020

Page n. 10/10

# 6232 – weber.tex beton design

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Information for users
Aysun Yılmaz
R&D Laboratory Responsible
Certification number:GBF01.18.03
Saint Gobain Weber Yapı Kimyasalları A.Ş.
Contact: aysun.yilmaz@weber.com.tr