

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 3 (replaces version 2)

Revision: 31.08.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **weberdry PUR basic**

Safety data sheet no.: XXP015611

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

The product is intended for industrial or professional use.

**Application of the substance / the mixture** Construction chemicals

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:**Saint-Gobain Weber Yapı Kim. San. ve Tic. A.S.  
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284  
35730 Kemalpaşa / Izmir  
TURKEY

Tel: +90 232 397 07 00

Fax: +90 232 397 08 00

#### 1.4 Emergency telephone number:

Tel: +90 232 397 07 13-07 84

National Poison Information Center (UZEM): 114

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3      H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1      H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT RE 2      H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1      H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2      H315 Causes skin irritation.

Eye Irrit. 2      H319 Causes serious eye irritation.

Skin Sens. 1      H317 May cause an allergic skin reaction.

Aquatic Chronic 3      H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

EUG

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 3 (replaces version 2)

Revision: 31.08.2021

**Trade name weberdry PUR basic**

(Contd. of page 1)

**Hazard pictograms**

GHS02 GHS08

**Signal word** Danger**Hazard-determining components of labelling:**

reaction mass of ethylbenzene and m-xylene and p-xylene  
m-tolylidene diisocyanate  
4,5-dichloro-2-octyl-2H-isothiazol-3-one

**Hazard statements**

H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317 May cause an allergic skin reaction.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H304 May be fatal if swallowed and enters airways.  
H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P331 Do NOT induce vomiting.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**2.3 Other hazards****Results of PBT and vPvB assessment**

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures**

**Description:** Mixture consisting of the following components.

(Contd. on page 3)

EUG

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 3 (replaces version 2)

Revision: 31.08.2021

**Trade name weberdry PUR basic**

(Contd. of page 2)

<b>Dangerous components:</b>		
EC number: 905-562-9 Reg.nr.: 01-2119488216-32-xxxx	reaction mass of ethylbenzene and m-xylene and p-xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412 Specific concentration limit: STOT RE 2; H373: C ≥ 10 %	≥15-<20%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17-xxxx	titanium dioxide ⚠ Carc. 2, H351	≥2-<3%
CAS: 26471-62-5 EINECS: 247-722-4 Index number: 615-006-00-4 Reg.nr.: 01-2119454791-34-xxxx	m-tolyldiene diisocyanate ⚠ Acute Tox. 2, H330; ⚠ Resp. Sens. 1, H334; Carc. 2, H351; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412, EUH204 Specific concentration limit: Resp. Sens. 1; H334: C ≥ 0.1 %	0.1-<0.5%
CAS: 64359-81-5 EINECS: 264-843-8	4,5-dichloro-2-octyl-2H-isothiazol-3-one ⚠ Acute Tox. 1, H330; ⚠ Skin Corr. 1, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ⚠ Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1; H314: C ≥ 5 % Skin Irrit. 2; H315: 0.025 % ≤ C < 5 % Eye Dam. 1; H318: C ≥ 3 % Eye Irrit. 2; H319: 0.025 % ≤ C < 3 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.0025-<0.025%

**SVHC** Void

**Additional information** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

Take affected persons out into the fresh air.

Seek immediate medical advice

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 3 (replaces version 2)

Revision: 31.08.2021

**Trade name weberdry PUR basic**

(Contd. of page 3)

Seek medical treatment in case of complaints.

**After skin contact**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact**

Rinse opened eye for several minutes under running water. Rinse liquid should be tempered (20-30°C).

Seek immediate medical advice.

**After swallowing**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

Seek immediate medical advice.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed or in case of vomiting, danger of entering the lungs

### SECTION 5: Firefighting measures

**5.1 Extinguishing media****Suitable extinguishing agents**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**For safety reasons unsuitable extinguishing agents** Water with full jet

**5.2 Special hazards arising from the substance or mixture**

Carbon dioxide (CO<sub>2</sub>)

Carbon monoxide (CO)

**5.3 Advice for firefighters****Protective equipment:**

Wear fully protective suit.

Mouth respiratory protective device.

**Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation.

Mouth respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

**6.2 Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

**6.3 Methods and material for containment and cleaning up:**

Absorb liquid components with liquid-binding material.

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents.

(Contd. on page 5)

EUG

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 3 (replaces version 2)

Revision: 31.08.2021

**Trade name weberdry PUR basic**

(Contd. of page 4)

Dispose of contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Send for recovery or disposal in suitable receptacles.

**6.4 Reference to other sections**

See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

Avoid contact with skin and eyes.  
Open and handle receptacle with care.  
Handle with care. Avoid jolting, friction and impact.  
Store in cool, dry place in tightly closed receptacles.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Do not spray onto a naked flame or any incandescent material.  
Flammable gas-air mixtures may form in empty receptacles.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage**

**Requirements to be met by storerooms and receptacles:**

Store in a cool location.  
Provide ventilation for receptacles.

**Information about storage in one common storage facility:** Store away from foodstuffs.

**Further information about storage conditions:**

Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.  
Store under lock and key and with access restricted to technical experts or their assistants only.

**7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

DNELs		
reaction mass of ethylbenzene and m-xylene and p-xylene		
Oral	Derived No Effect Level	12.5 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	212 mg/kgxday (worker systemic long term value)
		125 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	221 mg/m <sup>3</sup> (worker systemic long term value)
		442 mg/m <sup>3</sup> (worker systemic short term value)
		65.3 mg/m <sup>3</sup> (consumer systemic long term value)
		260 mg/m <sup>3</sup> (consumer systemic short term value)

(Contd. on page 6)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 3 (replaces version 2)

Revision: 31.08.2021

**Trade name weberdry PUR basic**

(Contd. of page 5)

PNECs	
reaction mass of ethylbenzene and m-xylene and p-xylene	
Predpokladaná koncentrácia bez účinku (PNEC)	0.327 mg/l (sea water rating factor) 0.327 mg/l (fresh water rating factor)
CAS No.	Designation of material % Type Value Unit
<b>CAS: 13463-67-7 titanium dioxide</b>	
AGW (Germany)	Long-term value: 1.25* 10** mg/m <sup>3</sup> 2(II);*alveolengängig**einatembare; AGS, DFG
GV (Denmark)	Long-term value: 6 mg/m <sup>3</sup> K, som Ti
LEP (Spain)	Long-term value: 10 mg/m <sup>3</sup>
TWA (Italy)	Long-term value: 10 mg/m <sup>3</sup> A4
VLE (Portugal)	Long-term value: 10 mg/m <sup>3</sup> A4; Irritação do TRI
OEL (Sweden)	Long-term value: 5 mg/m <sup>3</sup> totaldamm
<b>CAS: 26471-62-5 m-tolyldiene diisocyanate</b>	
MAK (Germany)	vgl. Abschn.XII
OEL (Sweden)	Short-term value: 0.04 mg/m <sup>3</sup> , 0.005 ppm Long-term value: 0.014 mg/m <sup>3</sup> , 0.002 ppm C, M, S
HTP (Finland)	Short-term value: 0.035 mg/m <sup>3</sup> NCO

### 8.2 Exposure controls

**Appropriate engineering controls** No further data; see item 7.

**Individual protection measures, such as personal protective equipment**

**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Store protective clothing separately.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale dust / smoke / mist.

**Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Combination of charcoal filter and particulate filter A2-P2 (EN 529)

**Hand protection**

Protective gloves against chemicals (standard EN 374-1)

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

(Contd. on page 7)

EUG

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 3 (replaces version 2)

Revision: 31.08.2021

**Trade name weberdry PUR basic**

(Contd. of page 6)

Due to missing tests no recommendation to the glove material can be given for the product/ the mixture/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

Butyl rubber, BR

Fluorocarbon rubber (FKM-Viton)

Recommended thickness of the material:  $\geq 0.5$  (BR) ; 0.4 (FKM-Viton) mm

Recommendation: contaminated gloves should be disposed of.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

The determined breakthrough times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the breakthrough time, is recommended.

For the mixture of chemicals mentioned below the breakthrough time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

**Eye/face protection**

Tightly sealed goggles

Protective eyewear (standard EN 166)

**Body protection:**

Boots

Chemically resistant protective work clothing (EN 14605)

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

<b>Colour:</b>	Various colours
<b>Odour:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.
<b>Melting point/freezing point:</b>	Undetermined.
<b>Boiling point or initial boiling point and boiling range</b>	130-150 °C (EC No. 905-562-9)
<b>Flammability</b>	Not applicable.
<b>Lower and upper explosion limit</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
<b>Flash point:</b>	30 °C (Pensky-Martens)
<b>Auto-ignition temperature:</b>	Product is not selfigniting.
<b>Decomposition temperature:</b>	Not determined.
<b>pH</b>	Not applicable.
<b>Viscosity:</b>	
<b>Kinematic viscosity at 23 °C</b>	374 s (ISO 2431/Flow time tISO)
<b>dynamic:</b>	Not determined.
<b>Solubility</b>	
<b>Water:</b>	Not miscible or difficult to mix

(Contd. on page 8)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 3 (replaces version 2)

Revision: 31.08.2021

**Trade name weberdry PUR basic**

(Contd. of page 7)

<b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
<b>Vapour pressure:</b>	Not determined.
<b>Density and/or relative density</b>	
<b>Density at 20 °C:</b>	1.44 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined.
<b>Bulk density:</b>	Not applicable.
<b>Vapour density</b>	Not determined.

**9.2 Other information**

**Appearance:**

**Form:** Viscous

**Important information on protection of health and environment, and on safety.**

**Ignition temperature:** 488 °C (Ec No. 905-562-9)

**Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

**Minimum ignition energy**

**Solvent separation test:** <1 % (UN Part III, par. 32.5.1)

**EU-VOC (g/L)** 249.0 g/l

**Change in condition**

**Softening point/range**

**Oxidising properties** Not considered as oxidising.

**Evaporation rate** Not determined.

**Information with regard to physical hazard classes**

<b>Explosives</b>	Void
<b>Flammable gases</b>	Void
<b>Aerosols</b>	Void
<b>Oxidising gases</b>	Void
<b>Gases under pressure</b>	Void
<b>Flammable liquids</b>	
Flammable liquid and vapour.	
<b>Flammable solids</b>	Void
<b>Self-reactive substances and mixtures</b>	Void
<b>Pyrophoric liquids</b>	Void
<b>Pyrophoric solids</b>	Void
<b>Self-heating substances and mixtures</b>	Void
<b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
<b>Oxidising liquids</b>	Void
<b>Oxidising solids</b>	Void
<b>Organic peroxides</b>	Void
<b>Corrosive to metals</b>	Void
<b>Desensitised explosives</b>	Void

**SECTION 10: Stability and reactivity**

**10.1 Reactivity** Not reactive under normal conditions of use

(Contd. on page 9)



**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 3 (replaces version 2)

Revision: 31.08.2021

**Trade name weberdry PUR basic**

(Contd. of page 8)

**10.2 Chemical stability** Stable at recommended storage conditions

**Thermal decomposition / Conditions to be avoided:**

Stable at environment temperature.

To avoid thermal decomposition do not overheat.

**10.3 Possibility of hazardous reactions** No dangerous reactions known

**10.4 Conditions to avoid** Avoid heat, sparkles, naked flame or other sources of ignition.

**10.5 Incompatible materials:** No further relevant information available.

**10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:**

Components	Type	Value	Species
Dermal	LD50	6,128 mg/kg (Calculation)	
Inhalative	LC50/4 h	27.5 mg/l (Calculation)	

**CAS: 1317-65-3 limestone**

Oral	LD50	>5,000 mg/kg (Rat)	
------	------	--------------------	--

**reaction mass of ethylbenzene and m-xylene and p-xylene**

Oral	LD50	>3,523 mg/kg (Rat)	
Dermal	LD50	>12,126 mg/kg (Rabbit)	
Inhalative	LC50/4 h	>27 mg/l (Rat)	

**CAS: 13463-67-7 titanium dioxide**

Oral	LD50	>10,000 mg/kg (Rat)	
------	------	---------------------	--

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/irritation** Causes serious eye irritation.

**Respiratory or skin sensitisation**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure** Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**11.2 Information on other hazards**

**Endocrine disrupting properties**

None of the ingredients is listed.

EUG

(Contd. on page 10)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 3 (replaces version 2)

Revision: 31.08.2021

**Trade name weberdry PUR basic**

(Contd. of page 9)

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity:** Harmful to aquatic life with long lasting effects.

Type of test	Effective concentration	Method	Assessment
<b>CAS: 1317-65-3 limestone</b>			
LC50/96h	>10,000 mg/l	(Oncorhynchus mykiss (Rainbow trout))	
EC50/48h	>1,000 mg/l	(Daphnia magna)	
EC50/72h	>200 mg/l	(Algae)	
<b>reaction mass of ethylbenzene and m-xylene and p-xylene</b>			
LC50/96h	>2.6 mg/l	(Fish)	
EC50/24h	96 mg/l	(Activated sludge)	
EC50/72h	4.6-4.9 mg/l	(Algae)	
NOEC (21d)	1.57 mg/l	(Daphnia magna)	
<b>CAS: 13463-67-7 titanium dioxide</b>			
LC50/48h	500 mg/l	(Daphnia magna)	
EC50/72h	100 mg/l	(Algae)	
NOEC (72h)	100 mg/l	(Algae)	
NOEC (14d)	0.87-1.1 mg/l	(Fish)	
NOEC (21d)	5 mg/l	(Daphnia magna)	

**12.2 Persistence and degradability** No further relevant information available.

**Behaviour in environmental systems:**

<b>Components:</b>	
<b>reaction mass of ethylbenzene and m-xylene and p-xylene</b>	
DT50-value (Degradation Half Time)	2 day

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

**12.5 Results of PBT and vPvB assessment**

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**12.7 Other adverse effects**

**Remark:** Harmful to fish

**Additional ecological information:**

**General notes:**

The product contains materials that are harmful to the environment.

Harmful to aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

EUG

(Contd. on page 11)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 3 (replaces version 2)

Revision: 31.08.2021

**Trade name weberdry PUR basic**

(Contd. of page 10)

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Recommendation**

Dispose of the product in accordance with national and local regulations.  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Contact manufacturer for recycling information.

**European waste catalogue**



Possible waste code. The concrete waste code depends on the source of the waste.

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP14	Ecotoxic

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

<b>14.1 UN number or ID number</b> ADR, IMDG, IATA	UN1866
<b>14.2 UN proper shipping name</b> ADR IMDG, IATA	1866 RESIN SOLUTION RESIN SOLUTION
<b>14.3 Transport hazard class(es)</b> ADR	
	
<b>Class</b> <b>Label</b>	3 (F1) Flammable liquids. 3
<b>IMDG, IATA</b>	
	
<b>Class</b> <b>Label</b>	3 Flammable liquids. 3
<b>14.4 Packing group</b> ADR, IMDG, IATA	III
<b>14.5 Environmental hazards:</b>	Not applicable.

(Contd. on page 12)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 3 (replaces version 2)

Revision: 31.08.2021

**Trade name weberdry PUR basic**

(Contd. of page 11)

<b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
<b>Hazard identification number (Kemler code):</b>	30
<b>EMS Number:</b>	F-E, <u>S</u> -E
<b>Stowage Category</b>	A
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
<b>Transport/Additional information:</b>	
<b>ADR</b>	
<b>Limited quantities (LQ)</b>	5L
<b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>Transport category</b>	3
<b>Tunnel restriction code</b>	D/E
<b>Remarks:</b>	Not subject to ADR Class 3 if packaging ≤ 5L according to ADR 2.2.3.1.5.2
<b>IMDG</b>	
<b>Limited quantities (LQ)</b>	5L
<b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>Remarks:</b>	Not subject to IMDG Class 3 if packaging ≤ 5L according to IMDG 2.3.2.5.
<b>IATA</b>	
<b>Remarks:</b>	Outside ADR/IMDG = UN 1866 - 3 (F1) -RESIN SOLUTION, flammable
<b>UN "Model Regulation":</b>	UN 1866 RESIN SOLUTION, 3, III

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No 1272/2008 (CLP)

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Directive 2004/42/CE (VOC), cf. section 9

**Labelling according to Regulation (EC) No 1272/2008** cf. section 2

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category** P5c FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 74

(Contd. on page 13)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 3 (replaces version 2)

Revision: 31.08.2021

**Trade name weberdry PUR basic**

(Contd. of page 12)

**DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

**REGULATION (EU) 2019/1148****Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.
- EUH204 Contains isocyanates. May produce an allergic reaction.

**Department issuing SDS:** Research and development**Contact:**

Esil Ulusoy

Chemist

SDS preparer (Certificate No: TÜV/01.260.02 - Validity date: 24.12.2023)

Saint Gobain Weber Yapı Kimyasalları A.Ş.

e-mail : esil.ulusoy@weber.com.tr

Elif Saraçoğlu

(Certificate No:TÜV/01.260.01 - Validity date 24.12.2023)

(Contd. on page 14)

EUG

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.09.2021

Version number 3 (replaces version 2)

Revision: 31.08.2021

**Trade name weberdry PUR basic**

(Contd. of page 13)

Barış Yıldırım

(Certificate No: TÜV/01.275.01 - Validity date 25.03.2024)

**Date of previous version: 17.02.2021****Version number of previous version: 2****Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 1: Acute toxicity – Category 1

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1: Skin corrosion/irritation – Category 1

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**\* Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.



This document was created with the Win2PDF "print to PDF" printer available at <http://www.win2pdf.com>

This version of Win2PDF 10 is for evaluation and non-commercial use only.

This page will not be added after purchasing Win2PDF.

<http://www.win2pdf.com/purchase/>