

weberart soft matt

Semi-matt interior paint

Technical DataSheet

Release date: 5/12/2017

Revision date: 6/20/2022

■ Product Description

Acrylic-based, semi-matt interior paint

■ Reference Standards

• TS 5808 • G marking • Public Works Pos No: 04.551/02, 04.551/03

■ Benefits

• Provides silky surface with its semi-matt formula • Can be wiped • Allows substrate to breathe • Odorless • High adherence and covering • Water repellent

■ Area of Use

• Used on interiors of all buildings for decorative purposes.



■ Substrates

• Interior walls; - Cement-based renders, - Concrete (**webertec R**, **webertec RK** or **webertec RM** applied), - Plaster render, gypsum block, plaster board substrates, - Gas concrete (gas concrete render or **webertec RM** applied), • Old painted substrates, • Please consult us for all other application substrates.

■ Preparation of Substrate

• Substrate should be clean, dry, smooth and sound.
• Substrates should be primed with **weberprim art** without diluting and application of **weberart soft matt** should be started at least 6 hours later.

■ Application Conditions

• Ambient temperature is between +5 °C and +30 °C • Avoid application in very damp and/or hot weather.

■ Application

- **weberart soft matt** should be diluted with water in the rate of 10 % for the first and second coat in brush and roller application, and should be mixed well until homogenous state is achieved.
- **weberart soft matt** should be applied to the entire substrate in two coats with lambskin roller or brush roller.
- Wait for minimum 6 hours between coats.

■ Tools

Lambskin roller and brush

■ TDS Consumption

8 m²/ l (for two layers)

■ Attention points

• Never use salty water. • Never add lime and similar foreign materials. • All tools used for application should be cleaned with water before drying

■ Technical specifications

Product Name	weberart soft matt
Product Type	liquid (density ~1,32 g/cm ³)
Drying time	6-24 hours
Finishes/Colors	96 colors
Wet Scrub Resistance	SINIF 1
Opacity	SINIF 2 (7 m ² /l)
Grain Size	İNCE
Glossiness	YARI MAT

■ Storage

Packaging	Net 15 l plastic buckets
Shelf life	1 year as of the production date in dry and moisturefree environment provided that packages will not be opened. Package should be kept tightly closed when not in use. Package should be protected against frosts

■ Safety Warning

- Use appropriate safety equipment (mask, gloves, glasses).
- Protect your eyes/face.
- Avoid direct contact with eyes and skin.
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Please read Material Safety Data Sheet (MSDS) for further safety information.
- Multiple pallets should not be stacked on top of each other during transportation and storage.

DISCLAIMER

Ürünün amacının dışında kullanılması ya da yukarıda belirtilen şartlara uyulmaması halinde oluşabilecek uygulama hatalarından **Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş.** sorumlu değildir.

The stated times apply for 20°C substrate and ambient temperature; increase at lower temperatures and decrease at higher temperatures. Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş. is not responsible for the application errors arising from use of product beyond its intended purpose of failure to comply with the foregoing application conditions and advice on the product.

Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş.

Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284 • 35730 Kemalpaşa • İzmir • Türkiye
Tel: +90 (232) 397 07 00 • www.tr.weber • info@weber.com.tr • Çözüm Hattı 444 6 990

