

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.05.2024

Version number 1

Revision: 14.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **weberfloor powercoat**

Safety data sheet no.: XXP018092

1.2 Relevant identified uses of the substance or mixture and uses advised against

The product is intended for professional or consumer use.

Application of the substance / the mixture Screed mortar for flooring

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Weber Yapı Kim. San. ve Tic. A.S.
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284
35730 Kemalpaşa / Izmir
TURKEY

Tel: +90 232 397 07 00

Fax: +90 232 397 08 00

1.4 Emergency telephone number:

Tel: +90 232 397 07 13-07 84

National Poison Information Center (UZEM): 114

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Results of in vitro- tests have shown that cement based mixtures with more than 1% of cement cause serious skin irritation and serious eye damage, therefore the classification of these mixtures regarding H315 and H318 is not based on the calculation of the ingredients or the pH in this case.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS05



GHS07

(Contd. on page 2)

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.05.2024

Version number 1

Revision: 14.05.2024

Trade name: weberfloor powercoat

(Contd. of page 1)

Signal word Danger

Hazard-determining components of labelling:

Cement, alumina, chemicals
cement portland, grey

Hazard statements

H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

The product contains silica sand with less than 1% of fine fraction and therefore is not classified as hazardous; however, pay attention when handling and follow the indications relating to personal protective equipment.

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.
vPvB: Does not contain vPvB substances.

Determination of endocrine-disrupting properties

Does not contain substances with endocrine-disrupting properties.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with non hazardous additions.

Dangerous components:

CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	25-50%
CAS: 65997-16-2 EINECS: 266-045-5	Cement, alumina, chemicals ☠ Eye Dam. 1, H318; ☠ Skin Irrit. 2, H315	10-20%
CAS: 7778-18-9 EINECS: 231-900-3 Reg.nr.: 01-2119444918-26-xxxx	calcium sulphate, different hydrate levels CaSO ₄ x n H ₂ O (n = 0; 1/2; 2) substance with a Community workplace exposure limit	5-10%

(Contd. on page 3)

EUG

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.05.2024

Version number 1

Revision: 14.05.2024

Trade name: weberfloor powercoat

(Contd. of page 2)

CAS: 1317-65-3 EINECS: 215-279-6 Reg.nr.: 01-2119486795-18-xxxx	calcium carbonate substance with a Community workplace exposure limit	2-5%
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335, EUH203 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 %	2-5%
CAS: 69012-64-2 EINECS: 273-761-1 Reg.nr.: 01-2119486866-17-xxxx	amorphous silica (fume) substance with a Community workplace exposure limit	1-2%
CAS: 1344-28-1 EINECS: 215-691-6 Reg.nr.: 01-2119529248-35-xxxx	aluminium oxide substance with a Community workplace exposure limit	1-2%

SVHC Void

Additional information

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 1%. The respirable fraction has an occupational exposure limit value (cf. section 8).

(CAS:13463-67-7) Titanium dioxide

Note 10 of CLP classification: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Never administer anything by mouth to an unconscious person.

If unconscious, place the patient in a stable side position and consult a doctor

After inhalation

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air and to be sure call for a doctor.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing Rinse mouth. DO NOT induce vomiting. If symptoms persist consult a doctor.

(Contd. on page 4)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.05.2024

Version number 1

Revision: 14.05.2024

Trade name: weberfloor powercoat

(Contd. of page 3)

4.2 Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire. Use foam, carbon dioxide, dry powder or water fog to extinguish.

5.2 Special hazards arising from the substance or mixture

The product is not flammable, it is not explosive, and does not enable or feed combustion in other materials.

5.3 Advice for firefighters

Protective equipment:

Use methods suitable to surrounding conditions.

Wear fully protective suit.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Ensure adequate ventilation.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose of contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Thorough dedusting.

Keep receptacles tightly sealed.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

(Contd. on page 5)

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.05.2024

Version number 1

Revision: 14.05.2024

Trade name: weberfloor powercoat

(Contd. of page 4)

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs		
CAS: 65997-16-2 Cement, alumina, chemicals		
Inhalative	Derived No Effect Level	2.5 mg/m ³ (worker systemic long term value) 5 mg/m ³ (worker systemic short term value)
CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO₄ x n H₂O (n = 0; 1/2; 2)		
Oral	Derived No Effect Level	1.52 mg/kgxday (consumer systemic long term value) 11.4 mg/kgxday (consumer systemic short term value)
Inhalative	Derived No Effect Level	21.17 mg/m ³ (worker systemic long term value) 5,082 mg/m ³ (worker systemic short term value) 5.29 mg/m ³ (consumer systemic long term value) 3,811 mg/m ³ (consumer systemic short term value)
CAS: 1317-65-3 calcium carbonate		
Oral	Derived No Effect Level	6.1 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	6.36 mg/m ³ (worker local long term value) 1.06 mg/m ³ (consumer local long term value)
CAS: 69012-64-2 amorphous silica (fume)		
Inhalative	Derived No Effect Level	0.3 mg/m ³ (worker local long term value)
CAS: 1344-28-1 aluminium oxide		
Oral	Derived No Effect Level	1.32 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	3 mg/m ³ (worker systemic long term value) 0.75 mg/m ³ (consumer systemic long term value)
PNECs		
CAS: 65996-69-2 Slags, ferrous metal, blast furnace		
Predicted No-Effect Concentration		1,000 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration		500 mg/l (sea water rating factor) 5,000 mg/l (fresh water rating factor)
CAS: 65997-16-2 Cement, alumina, chemicals		
Predicted No-Effect Concentration		260 mg/l (fresh water rating factor)

(Contd. on page 6)

EUG

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.05.2024

Version number 1

Revision: 14.05.2024

Trade name: weberfloor powercoat

(Contd. of page 5)

CAS No. / Designation of material / % / Type / Value / Unit	
CAS: 14808-60-7 Silicon dioxide (Quartz sand)	
BOELV (European Union)	Long-term value: 0.1* mg/m ³ *respirable fraction
MAK (Germany)	alveolengängige Fraktion
GV (Denmark)	Short-term value: 0.6* 0.2** mg/m ³ Long-term value: 0.3* 0.1** mg/m ³ *total.; **total, respirabel: K
LEP (Spain)	Long-term value: 0.05 mg/m ³ *Fracción resp:n,d,y
TWA (Italy)	Long-term value: 0.025 mg/m ³ A2, (j)
VLE (Portugal)	Long-term value: 0.025 mg/m ³ Resp.;A2; fibrose pulmonar; cancro do pulmão
OEL (Sweden)	Long-term value: 0.1 mg/m ³ C, M, respirabel fraktion
HTP (Finland)	Long-term value: 0.05 0.1* mg/m ³ alveolijae;*sitovat raja-arvot, pöly
CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO₄ x n H₂O (n = 0; 1/2; 2)	
MAK (Germany)	Long-term value: 4E** mg/m ³ alveoleng.: Abschn.IIIb.*einatembar:Abschn.Vf)/g)
LEP (Spain)	Long-term value: 10 mg/m ³ e
TWA (Italy)	Long-term value: 10 mg/m ³ (i)
VLE (Portugal)	Long-term value: 10 mg/m ³ Fração inalável; Sintomas nasais
CAS: 1317-65-3 calcium carbonate	
TWA (Italy)	Long-term value: 10 mg/m ³ (e)
CAS: 65997-15-1 cement portland, grey	
AGW (Germany)	Long-term value: 5 E mg/m ³ DFG
LEP (Spain)	Long-term value: 4 mg/m ³ fracción respirable: e, d
TWA (Italy)	Long-term value: 1 mg/m ³ (e, j), A4
VLE (Portugal)	Long-term value: 1 mg/m ³ Fração resp.;A4,função pulm.,sintomas resp.,asma
HTP (Finland)	Long-term value: 5* 1** mg/m ³ *hengittyvä pöly, **alveolijae

(Contd. on page 7)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.05.2024

Version number 1

Revision: 14.05.2024

Trade name: weberfloor powercoat

(Contd. of page 6)

CAS: 69012-64-2 amorphous silica (fume)

AGW (Germany)	Long-term value: 0.3 A mg/m ³ DFG, Y, 1
GV (Denmark)	Short-term value: 0.2 mg/m ³ Long-term value: 0.1 mg/m ³ K, respirabel
LEP (Spain)	Long-term value: 2* mg/m ³ *Fracción respirable: d
TWA (Italy)	Long-term value: (2) mg/m ³ (j); silice, fumi
VLE (Portugal)	Long-term value: 2 mg/m ³ Irritacao; febre

CAS: 1344-28-1 aluminium oxide

AGW (Germany)	Long-term value: 1.25* 10** mg/m ³ 2(II);*alveolengängig**einatembar; AGS, DFG, Y
GV (Denmark)	Short-term value: 10* 4** mg/m ³ Long-term value: 5* 2** mg/m ³ som Al, *total; **respirabel
LEP (Spain)	Long-term value: 10 mg/m ³
TWA (Italy)	Long-term value: 10 mg/m ³ A4 (e)
VLE (Portugal)	Long-term value: 1 mg/m ³ respirável;A4,Pneumoconiose,Irritação TRI,em Al
OEL (Sweden)	Long-term value: 5* 2** mg/m ³ som Al; *totaldamm **respirabelt damm

Additional Occupational Exposure Limit Values for possible hazards during processing:

Total inhalable dust: 10 mg/m³
Respirable dust (< 5 µm): 4 mg/m³
Quartz respirable dust (< 5 µm) : 0,15 mg/m³

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
Use a moisturising skin cream after processing the product.

Respiratory protection:

Short term filter device:
Filter P2.

Hand protection Protective gloves.

Material of gloves Nitrile impregnated cotton gloves complying with the standard EN 374-1.

(Contd. on page 8)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.05.2024

Version number 1

Revision: 14.05.2024

Trade name: weberfloor powercoat

(Contd. of page 7)

Eye/face protection Tightly sealed goggles
Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Solid.
Colour:	Grey
Odour:	Odourless
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	Undetermined.
Flammability	Product is not flammable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
pH	Mixture reacts violently with water.
Viscosity:	
Kinematic viscosity	Not applicable.
dynamic:	Not applicable.
Solubility	
Water:	Hardens when in contact with water.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not applicable.
Density and/or relative density	
Density at 20 °C:	1.24 g/cm ³ (DIN 51757)
	Not applicable.
Relative density	Not determined.
Bulk density:	2 kg/m ³
Vapour density	Not applicable.
Particle characteristics	
See section 3.	

9.2 Other information

Appearance:	
Form:	Powder
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not self-igniting.
Explosive properties:	Product does not present an explosion hazard.

(Contd. on page 9)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.05.2024

Version number 1

Revision: 14.05.2024

Trade name: weberfloor powercoat

(Contd. of page 8)

Minimum ignition energy	
Solvent content:	
Water:	0.0 %
EU-VOC (g/L)	
Solids content:	100.0 %
Change in condition	
Softening point/range	
Oxidising properties	Not determined.
Evaporation rate	Not applicable.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity Not reactive under normal conditions of use

10.2 Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with acids

Reacts with light alloys in the presence of moisture to form hydrogen

10.4 Conditions to avoid

Avoid water ingress/moisture during storage (the product will react with moisture and harden).

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

EUG

(Contd. on page 10)

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.05.2024

Version number 1

Revision: 14.05.2024

Trade name: weberfloor powercoat

(Contd. of page 9)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 65996-69-2 Slags, ferrous metal, blast furnace			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>4,000 mg/kg	(Rat)
CAS: 65997-16-2 Cement, alumina, chemicals			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)
CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO₄ x n H₂O (n = 0; 1/2; 2)			
Oral	LD50	>2,000 mg/kg	(Rat)
CAS: 1317-65-3 calcium carbonate			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)
CAS: 65997-15-1 cement portland, grey			
Dermal	LD50	>2,000 mg/kg	(Rabbit)

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye damage.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

Type of test	Effective concentration	Method	Assessment
CAS: 65996-69-2 Slags, ferrous metal, blast furnace			
LC50/96h	>100 mg/l	(Leuciscus idus (Orfe))	
LC0/96h	>100 mg/l	(Leuciscus idus (Orfe))	
EC50/72h	>90,000 mg/l	(Algae)	

(Contd. on page 11)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.05.2024

Version number 1

Revision: 14.05.2024

Trade name: weberfloor powercoat

(Contd. of page 10)

NOEC (72h)	50-100 mg/l (Algae)
NOEC (21d)	1,563 mg/l (Daphnia magna)
EC 0/48h	>100 mg /l (Daphnia magna)
CAS: 65997-16-2 Cement, alumina, chemicals	
LC50/96h	100 mg/l (Fish)
EC50/24h	6.4 mg/l (aquatic invertebrates)
EC50/48h	5.4 mg/l (aquatic invertebrates)
EC50/72h	3.6 mg/l (aquatic algae and cyanobacteria)
NOEC (72h)	2.6 mg/l (aquatic algae and cyanobacteria)
NOEC (48h)	3.4 mg/l (aquatic invertebrates)
CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO₄ x n H₂O (n = 0; 1/2; 2)	
LC50/48h	79-1,970 mg/l (aquatic invertebrates)
LC50/96h	79-2,980 mg/l (Fish)
EC50/72h	>79 mg/l (aquatic algae and cyanobacteria)
CAS: 1317-65-3 calcium carbonate	
LC50/96h	>100 mg/l (Fish)
EC50/48h	>100 mg/l (aquatic invertebrates)
EC50/72h	>14 mg/l (aquatic algae and cyanobacteria)
CAS: 69012-64-2 amorphous silica (fume)	
LC50/96h	100 mg/l (Fish)
EC50/24h	>1,003 mg/l (aquatic invertebrates)
EC50/72h	4,200 mg/l (Algae)
NOEC (72h)	323 mg/l (aquatic algae and cyanobacteria)
NOEC (21d)	100 mg/l (aquatic invertebrates)

12.2 Persistence and degradability No further relevant information available.

Method

CAS: 1317-65-3 calcium carbonate

Biod. (28 days) | >90 %

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

(Contd. on page 12)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.05.2024

Version number 1

Revision: 14.05.2024

Trade name: weberfloor powercoat

(Contd. of page 11)

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment	
CAS: 65996-69-2 Slags, ferrous metal, blast furnace	
EC 50 (3h)	>10,000 mg/l (Activated sludge)
CAS: 65997-16-2 Cement, alumina, chemicals	
EC 50 (3h)	1,000 mg/l (microorganisms)
CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO₄ x n H₂O (n = 0; 1/2; 2)	
EC 50 (3h)	>1,000 mg/l (microorganisms)
CAS: 1317-65-3 calcium carbonate	
EC 50 (3h)	>1,000 mg/l (microorganisms)

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish.
Possible waste code 17 09 04.
Dispose of the product in accordance with national and local regulations.

European waste catalogue

10 13 11	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10
10 13 14	waste concrete and concrete sludge
HP4	Irritant - skin irritation and eye damage

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleaning agent:

Water, if necessary together with cleansing agents.
Thoroughly shake out sacks.

SECTION 14: Transport information

14.1 UN number or ID number ADR, IMDG, IATA	Void
14.2 UN proper shipping name ADR, IMDG, IATA	Void

(Contd. on page 13)

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.05.2024

Version number 1

Revision: 14.05.2024

Trade name: weberfloor powercoat

(Contd. of page 12)

14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII Entry no. 47 Chromium VI compounds)

Conditions of restriction: 47

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 14)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.05.2024

Version number 1

Revision: 14.05.2024

Trade name: weberfloor powercoat

(Contd. of page 13)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

EUH203 Contains chromium (VI). May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--	--

Department issuing SDS: Research and development

Contact:

Necati Utku Erol

(Sertifika No: TÜV/01.336.07 - Validity date 31.12.2023)

Barış Yıldırım

(Sertifika No: TÜV/01.275.01 - Validity date 25.03.2024)

Sesil Genç

(Sertifika No: TÜV/01.311.11 – Validity date 04.11.2024)

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 15)

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.05.2024

Version number 1

Revision: 14.05.2024

Trade name: weberfloor powercoat

(Contd. of page 14)

Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

EUG



This document was created with the Win2PDF "print to PDF" printer available at <http://www.win2pdf.com>

This version of Win2PDF 10 is for evaluation and non-commercial use only.

This page will not be added after purchasing Win2PDF.

<http://www.win2pdf.com/purchase/>