

## Safety Data Sheet

This SDS is an English translation of Regulation (EU) n° 2015/830,  
without any country-specific legislation

### IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

**1.1 Product identifier: StenAst S - Silane based primer**

**Trade name: weberprim PU**

**Safety data sheet no.:**

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Non-applicable

**Tavsiye edilmeyen kullanımlar:**

Relevant uses: Primers. For professional users/industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**

Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.

Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284

35730 Kemalpaşa / İzmir

TÜRKİYE

Tel: +90 232 397 07 00

Fax: +90 232 397 08 00

**1.4 Emergency telephone number:**

Tel: +90 232 397 07 13-07 84

Ulusal Zehir Danışma Merkezi (UZEM): 114

### HAZARDS IDENTIFICATION

**2.1 Classification of the substance or mixture:**



Acute Tox. 4: Acute toxicity, Category 4, H312+H332

Eye Dam. 1: Serious eye damage, Category 1, H318

Flam. Liq. 3: Flammable liquids, Category 3, H226

Skin Corr. 1B: Skin corrosion, Category 1B, H314

**2.2 Label elements:**

**CLP Regulation (EC) No 1272/2008:**

**Substances that contribute to the classification**

Xylene; 3-aminopropyltriethoxysilane

**Danger**



**Acute Tox. 4: H312+H332** - Harmful in contact with skin or if inhaled.

**Flam. Liq. 3: H226** - Flammable liquid and vapour.

**Skin Corr. 1B: H314** - Causes severe skin burns and eye damage.

(Continued on page 2)

## Safety Data Sheet

This SDS is an English translation of Regulation (EU) n° 2015/830,  
without any country-specific legislation

**Ticari adı: weberprim PU / StenAst S - Silane based primer**

(Continued from page 1)

**Precautionary statements:**

- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
- P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
- P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

**2.3 Other hazards:**



**Product fails to meet PBT/vPvB criteria**

### COMPOSITION/INFORMATION ON INGREDIENTS

**3.2 Mixture:**

Chemical description: Polymer/s

**Components:** In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains: Identification

Identification	Chemical name/Classification	Concentration
<b>CAS: 1330-20-7</b> <b>EC: 215-535-7</b> <b>Index: 601-022-00-9</b>	<b>Xylene<sup>(1)</sup></b>	<b>75 - &lt;100 %</b>
	Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning! 	
<b>CAS: 919-30-2</b> <b>EC: 213-048-4</b> <b>Index: 612-108-00-0</b>	<b>3-aminopropyltriethoxysilane<sup>(1)</sup></b>	<b>2.5 - &lt;10 %</b>
	Regulation 1272/2008 Acute Tox. 4: H302; Skin Corr. 1B: H314 - Danger! 	

## Safety Data Sheet

This SDS is an English translation of Regulation (EU) n° 2015/830,  
without any country-specific legislation

Ticari adı: weberprim PU / StenAst S - Silane based primer

### FIRST AID MEASURES

#### 4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

##### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

##### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

##### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

##### By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and also risk damage to the respiratory system through inhalation. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

### FIREFIGHTING MEASURES

#### 5.1 Extinguishing media:

##### Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

##### Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

(Continued on page 4)

## Safety Data Sheet

This SDS is an English translation of Regulation (EU) n° 2015/830,  
without any country-specific legislation

**Ticari adı: weberprim PU / StenAst S - Silane based primer**

(Continued from page 3)

### FIREFIGHTING MEASURES

#### **5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### **5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### ACCIDENTAL RELEASE MEASURES

#### **6.1 Personal precautions, protective equipment and emergency procedures:**

##### **For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

##### **For emergency responders:**

See section 8.

#### **6.2 Environmental precautions:**

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

#### **6.3 Methods and material for containment and cleaning up:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### **6.4 Reference to other sections:**

See sections 8 and 13.

## Safety Data Sheet

This SDS is an English translation of Regulation (EU) n° 2015/830,  
without any country-specific legislation

Ticari adı: weberprim PU / StenAst S - Silane based primer

### HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used. Technical recommendations for the prevention of fires and explosions Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges.

**Against the possibility of electrostatic charges:** ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

#### Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

#### Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

#### 7.2 Conditions for safe storage, including any incompatibilities:

##### Technical measures for storage

Minimum Temp.: 0 °C

Maximum Temp.: 30 °C

Maximum time: 12 Months

##### General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

#### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Identification	Occupational exposure limits		
	Xylene	IOELV (8h)	50 ppm
CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>

(Continued on page 6)

## Safety Data Sheet

This SDS is an English translation of Regulation (EU) n° 2015/830,  
without any country-specific legislation

**Ticari adı: weberprim PU / StenAst S - Silane based primer**

(Continued from page 5)

### EXPOSURE CONTROLS/PERSONAL PROTECTION

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
3-aminopropyltriethoxysilane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 919-30-2	Dermal	Non-applicable	Non-applicable	2 mg/kg	Non-applicable
EC: 213-048-4	Inhalation	Non-applicable	Non-applicable	14 mg/m <sup>3</sup>	Non-applicable

**DNEL- değerleri (nüfus)**

Kimlik		Kısa süreli maruziyet		Uzun Süreli Maruziyet	
		Systemic	Local	Systemic	Local
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>
3-aminopropyltriethoxysilane	Oral	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
CAS: 919-30-2	Dermal	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
EC: 213-048-4	Inhalation	Non-applicable	Non-applicable	3,5 mg/m <sup>3</sup>	Non-applicable

**PNEC:**

Kimlik					
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L	
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L	
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg	
3-aminopropiltriethoksisilan	STP	1,3 mg/L	Fresh water	Non-applicable	
CAS: 919-30-2	Soil	2,31 mg/kg	Marine water	Non-applicable	
EC: 213-048-4	Intermittent	0,327 mg/L	Sediment (Fresh water)	Non-applicable	
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable	

**8.2 Exposure controls:**

(Continued on page 7)

## Safety Data Sheet

This SDS is an English translation of Regulation (EU) n° 2015/830,  
without any country-specific legislation

Ticari adı: weberprim PU / StenAst S - Silane based primer

(Continued from page 6)

### Maruz kalma kontrolleri / kişisel korunma

#### Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

#### Respiratory protection

Mandatory respiratory tract protection

Filter mask for gases and vapours

Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

#### Specific protection for the hands

Mandatory hand protection

Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE),

Breakthrough time: > 480 min, Thickness: 0.062 mm)

Replace the gloves at any sign of deterioration.

#### Ocular and facial protection

Mandatory face protection

Face shield

Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

#### Body protection

Mandatory complete body protection

Disposable clothing for protection against chemical risks, with antistatic and fireproof properties

For professional use only. Clean periodically according to the manufacturer's instructions.

#### Mandatory foot protection

Safety footwear for protection against chemical risk, with antistatic and heat resistant properties

Replace boots at any sign of deterioration.

#### Additional emergency measures

Emergency shower

Eyewash stations

#### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

#### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 95 % weight

V.O.C. density at 20 °C: 828,2 kg/m<sup>3</sup> (828,2 g/L)

Average carbon number: 8

Average molecular weight: 106,2 g/mol

## Safety Data Sheet

This SDS is an English translation of Regulation (EU) n° 2015/830,  
without any country-specific legislation

**Ticari adı: weberprim PU / StenAst S - Silane based primer**

### PHYSICAL AND CHEMICAL PROPERTIES

**9.1 Information on basic physical and chemical properties:**

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Transparent
Colour:	Not available
Odour:	Alcohol
Odour threshold:	Non-applicable *

**Volatility:**

Boiling point at atmospheric pressure:	140 °C
Vapour pressure at 20 °C:	729 Pa
Vapour pressure at 50 °C:	4035,86 Pa (4,04 kPa)
Evaporation rate at 20 °C:	Non-applicable *

**Product description:**

Density at 20 °C:	871,8 kg/m <sup>3</sup>
Relative density at 20 °C:	0,872
Dynamic viscosity at 20 °C:	0,55 cP
Kinematic viscosity at 20 °C:	0,63 mm <sup>2</sup> /s
Kinematic viscosity at 40 °C:	Non-applicable *

**Concentration:**

pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

**Flammability:**

Flash Point:	25 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	300 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

**Particle characteristics:**

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

**9.2 Other information:**

**Information with regard to physical hazard classes:**

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

(Continued on page 9)

## Safety Data Sheet

This SDS is an English translation of Regulation (EU) n° 2015/830,  
without any country-specific legislation

Ticari adı: weberprim PU / StenAst S - Silane based primer

(Continued from page 8)

### PHYSICAL AND CHEMICAL PROPERTIES

Corrosive to metals: Non-applicable \*  
Heat of combustion: Non-applicable \*  
Aerosols-total percentage (by mass)  
of flammable components: Non-applicable \*

**Other safety characteristics:**

Surface tension at 20 °C: Non-applicable \*  
Refraction index: Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

### STABILITY AND REACTIVITY

**10.1 Reactivity:** No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:** Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:** Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:** Applicable for handling and storage at room temperature:

Shock and friction: Not applicable

Contact with air: Not applicable

Increase in temperature: Risk of combustion

Sunlight: Avoid direct impact

Humidity: Not applicable

**10.5 Kaçınılması gereken maddeler:**

Acids: Avoid strong acids

Water: Not applicable

Oxidising materials: Avoid direct impact

Combustible materials: Not applicable

Others: Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

### TOXICOLOGICAL INFORMATION

**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

(Continued on page 10)

## Safety Data Sheet

This SDS is an English translation of Regulation (EU) n° 2015/830,  
without any country-specific legislation

Ticari adı: weberprim PU / StenAst S - Silane based primer

(Continued from page 9)

### TOXICOLOGICAL INFORMATION

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

#### Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.

#### Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

#### Contact with the skin and the eyes (acute effect):

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
- Contact with the eyes: Produces serious eye damage after contact.

#### CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

IARC: Xylene (3)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

#### Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

#### Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

#### Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

#### Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

(Continued on page 11)

## Safety Data Sheet

This SDS is an English translation of Regulation (EU) n° 2015/830,  
without any country-specific legislation

**Ticari adı: weberprim PU / StenAst S - Silane based primer**

(Continued from page 10)

### TOXICOLOGICAL INFORMATION

#### Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
3-aminopropyltriethoxysilane CAS: 919-30-2 EC: 213-048-4	LD50 oral LD50 dermal LC50 inhalation	1491 mg/kg 4000 mg/kg Non-applicable	Rat Rabbit
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral LD50 dermal LC50 inhalation	2100 mg/kg 1100 mg/kg 11 mg/L (4 h) (ATEi)	Rat Rat

### ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

#### 12.1 Toxicity:

##### Acute toxicity:

Identification	Concentration		Species	Genus
3-aminopropyltriethoxysilane CAS: 919-30-2 EC: 213-048-4	LC50 EC50 EC50	Non-applicable 331 mg/L (48 h) 603 mg/L (72 h)	Daphnia magna Scenedesmus subspicatus	Crustacean Algae

##### Chronic toxicity:

Identification	Concentration		Species	Genus
Xylene CAS: 1330-20-7 EC: 215-535-7	NOEC NOEC	1,3 mg/L 1,17 mg/L	Oncorhynchus mykiss Ceriodaphnia dubia	Fish Crustacean

#### 12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Xylene CAS: 1330-20-7 EC: 215-535-7	BOİ5 KOİ BOİ5/KOİ	Non-applicable Non-applicable Non-applicable	Concentration Period % Biodegradable	Non-applicable 28 days 88 %
3-aminopropyltriethoxysilane CAS: 919-30-2 EC: 213-048-4	BOİ5 KOİ BOİ5/KOİ	Non-applicable Non-applicable Non-applicable	Concentration Period % Biodegradable	100 mg/L 28 days 54 %

## Safety Data Sheet

This SDS is an English translation of Regulation (EU) n° 2015/830,  
without any country-specific legislation

Ticari adı: weberprim PU / StenAst S - Silane based primer

### DISPOSAL CONSIDERATIONS

#### Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated  
Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

### TRANSPORT INFORMATION

#### Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

<b>14.1 UN number:</b>	UN1307
<b>14.2 UN proper shipping name:</b>	XYLENES
<b>14.3 Transport hazard class(es):</b>	<b>3</b>
Labels:	3
<b>14.4 Packing group:</b>	III
<b>14.5 Environmental hazards:</b>	No
<b>14.6 Special precautions for user</b>	
Special regulations:	Non-applicable
Tunnel restriction code:	D/E
Physico-Chemical properties:	see section 9
Limited quantities:	5 L
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC</b>	Non-applicable

#### Code:

#### Transport of dangerous goods by sea:

With regard to IMDG 39-18:

<b>14.1 UN number:</b>	UN1307
<b>14.2 UN proper shipping name:</b>	XYLENES
<b>14.3 Transport hazard class(es):</b>	<b>3</b>
Labels:	3
<b>14.4 Packing group:</b>	III
<b>14.5 Marine pollutant:</b>	No
<b>14.6 Special precautions for user</b>	
Special regulations:	223
EmS Codes:	F-E, S-D
Physico-Chemical properties:	see section 9
Limited quantities:	5 L
Segregation group:	Non-applicable
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC</b>	Non-applicable

#### Code:

(Continued on page 13)

## Safety Data Sheet

This SDS is an English translation of Regulation (EU) n° 2015/830,  
without any country-specific legislation

**Ticari adı: weberprim PU / StenAst S - Silane based primer**

### TRANSPORT INFORMATION

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2021:

- 14.1 UN number:** UN1307
- 14.2 UN proper shipping name:** XYLENES
- 14.3 Transport hazard class(es):** **3**
- Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
- Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

### REGULATORY INFORMATION

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH):

Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date:

Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

(Continued on page 14)

## Safety Data Sheet

This SDS is an English translation of Regulation (EU) n° 2015/830,  
without any country-specific legislation

**Ticari adı: weberprim PU / StenAst S - Silane based primer**

### ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

#### 12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF Pow Log Potential	9 2.77 Low
3-aminopropyltriethoxysilane CAS: 1330-20-7 EC: 215-535-7	BCF Pow Log Potential	1 0,1 Low

#### 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc Conclusion Surface tension	202 Moderate Non-applicable	Henry Dry soil Moist soil	524,86 Pa·m <sup>3</sup> /mol Yes Yes

#### 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

#### 12.6 Other adverse effects:

Not described

### DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

Identification	Description	Waste class (Regulation (EU) No 1357/2014)
04 02 14*	wastes from finishing containing organic solvents	Dangerous

#### Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP6 Acute Toxicity, HP8 Corrosive

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2(Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

## Safety Data Sheet

This SDS is an English translation of Regulation (EU) n° 2015/830,  
without any country-specific legislation

Ticari adı: weberprim PU /StenAst S - Silane based primer

(Continued from page 13)

### REGULATORY INFORMATION

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

#### Other legislation:

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

### OTHER INFORMATION

#### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

#### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: Non-applicable

Texts of the legislative phrases mentioned in section 2:

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

H312+H332: Harmful in contact with skin or if inhaled.

H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed.

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Classification procedure:

Skin Corr. 1B: Calculation method

Eye Dam. 1: Calculation method

Calculation method: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.