

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 29.12.2021

Version number 1

Revision: 22.08.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **weber.rep ep grout - component A**

Safety data sheet no.: XXP014599-a

1.2 Relevant identified uses of the substance or mixture and uses advised against

The product is intended for industrial or professional use.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Weber Yapı Kim. San. ve Tic. A.S.
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284
35730 Kemalpaşa / Izmir
TURKEY

Tel: +90 232 397 07 00

Fax: +90 232 397 08 00

1.4 Emergency telephone number:

Tel: +90 232 397 07 13-07 84

National Poison Information Center (UZEM): 114

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS07 GHS09

Signal word Warning

Hazard-determining components of labelling:

Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700)

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Hazard statements

H315 Causes skin irritation.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 29.12.2021

Version number 1

Revision: 22.08.2019

Trade name weber.rep ep grout - component A

(Contd. of page 1)

H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P391 Collect spillage.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards
Results of PBT and vPvB assessment
PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures
Description: Mixture of substances listed below with non hazardous additions.

Dangerous components:

CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-xxxx	Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Skin Irrit. 2; H315: C \geq 5 % Eye Irrit. 2; H319: C \geq 5 %	50-75%
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-21119454392-40-xxxx	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317, EUH205	25-50%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22-xxxx	oxirane, mono[(C12-14-alkyloxy)methyl] derivs ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	10-20%

SVHC Void

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures
General information

Immediately remove any clothing soiled by the product.
 Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 29.12.2021

Version number 1

Revision: 22.08.2019

Trade name weber.rep ep grout - component A

(Contd. of page 2)

After inhalation

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Rinse liquid should be tempered (20-30°C).

After swallowing If symptoms persist consult a doctor.**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media**Suitable extinguishing agents**CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

5.3 Advice for firefighters**Protective equipment:** No special measures required.**Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Not required.**6.2 Environmental precautions:**

The product must not get into watercourses

or into the soil.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

Suppress gases/fumes/haze with water spray.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection: No special measures required.

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 29.12.2021

Version number 1

Revision: 22.08.2019

Trade name weber.rep ep grout - component A

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions: None.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs

CAS: 25068-38-6 Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700)

Oral	Derived No Effect Level	0.75 mg/kgxday (consumer systemic long term value) 0.75 mg/kgxday (consumer systemic short term value)
Dermal	Derived No Effect Level	8.33 mg/kgxday (worker systemic long term value) 8.33 mg/kgxday (worker systemic short term value) 3.571 mg/kgxday (consumer systemic long term value) 3.571 mg/kgxday (consumer systemic short term value)
Inhalative	Derived No Effect Level	12.3 mg/m ³ (worker systemic long term value) 12.3 mg/m ³ (worker systemic short term value)

CAS: 9003-36-5 Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Oral	Derived No Effect Level	6.25 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	104.15 mg/kgxday (worker systemic long term value) 62.5 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	23.39 mg/m ³ (worker systemic long term value) 8.7 mg/m ³ (consumer systemic long term value)

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Oral	Derived No Effect Level	0.5 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	1 mg/kgxday (worker systemic long term value) 0.5 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	3.6 mg/m ³ (worker systemic long term value) 0.87 mg/m ³ (consumer systemic long term value)

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not eat or drink while working.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

(Contd. on page 5)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 29.12.2021

Version number 1

Revision: 22.08.2019

Trade name weber.rep ep grout - component A

(Contd. of page 4)

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Use a moisturising skin cream after processing the product.

Respiratory protection:

Not necessary if room is well-ventilated.

Short term filter device:

Filter AX.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection Protective gloves.

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Nitrile rubber, NBR

Eye/face protection Safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	Undetermined.
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	>60 °C
Auto-ignition temperature:	Product is not selfigniting.
Decomposition temperature:	Not determined.
pH	Not applicable.
Viscosity:	
Kinematic viscosity	Not determined.
dynamic:	Not determined.
Solubility	
Water:	Slightly soluble
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density:	Not determined
Relative density	Not determined.
Bulk density:	Not applicable.
Vapour density	Not determined.

9.2 Other information None.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 29.12.2021

Version number 1

Revision: 22.08.2019

Trade name weber.rep ep grout - component A

(Contd. of page 5)

Appearance:
Form: Pasty

Important information on protection of health and environment, and on safety.
Ignition temperature: Not determined.

Explosive properties: Product does not present an explosion hazard.

Minimum ignition energy:
Solvent separation test: Not determined

EU-VOC (%) 1.7379 %

EU-VOC (g/L) 17.3787 g/l

Change in condition
Softening point/range
Oxidising properties Not determined.

Evaporation rate Not determined.

Information with regard to physical hazard classes
Explosives Void

Flammable gases Void

Aerosols Void

Oxidising gases Void

Gases under pressure Void

Flammable liquids Void

Flammable solids Void

Self-reactive substances and mixtures Void

Pyrophoric liquids Void

Pyrophoric solids Void

Self-heating substances and mixtures Void

Substances and mixtures, which emit flammable gases in contact with water Void

Oxidising liquids Void

Oxidising solids Void

Organic peroxides Void

Corrosive to metals Void

Desensitised explosives Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 29.12.2021

Version number 1

Revision: 22.08.2019

Trade name weber.rep ep grout - component A

(Contd. of page 6)

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 25068-38-6 Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)			
Oral	LD50	>5,000 mg/kg (Rat)	
Dermal	LD50	>2,000 mg/kg (Rabbit)	
CAS: 9003-36-5 Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol			
Oral	LD50	>5,000 mg/kg (Rat)	
Dermal	LD50	>2,000 mg/kg (Rabbit)	
CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs			
Oral	LD50	26,800 mg/kg (Rat)	
Dermal	LD50	>4,000 mg/kg (Rabbit)	
		26,800 mg/kg (Rat)	

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.**11.2 Information on other hazards****Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity**Aquatic toxicity:** Toxic to aquatic life with long lasting effects (H411)

Type of test	Effective concentration	Method	Assessment
CAS: 25068-38-6 Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)			
LC50/96h	2 mg/l (Leuciscus idus (Orfe)) 1.3 mg/l (Fish)		
EC50/24h	4.6 mg/l (Daphnia magna)		
EC50/48h	1.8 mg/l (Daphnia magna)		
EC50/96h	220 mg/l (Selenastrum capricornutum (Green algae))		
NOEC (21d)	0.3 mg/l (Daphnia magna)		
CAS: 9003-36-5 Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol			
LC50/48h	2.55 mg/l (Daphnia magna)		
LC50/96h	2.54 mg/l (Leuciscus idus (Orfe))		

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 29.12.2021

Version number 1

Revision: 22.08.2019

Trade name weber.rep ep grout - component A

(Contd. of page 7)

EC50/48h	2.55 mg/l (Daphnia magna)
EC50/96h	2.54 mg/l (Leuciscus idus (Orfe))
CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs	
LC50/96h	>100 mg/l (Fish)
EC50/48h	7.2 mg/l (Daphnia magna)
NOEC (72h)	500 mg/l (Algae)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark:

The product contains substances which are toxic to fishes and bacteria.

Harmful to fish

Behaviour in sewage processing plants:

Type of test	Effective concentration	Method	Assessment
CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs			
EC 50 (3h)	100 mg/l	(Activated sludge)	

Additional ecological information:

General notes:

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Curing of the product by mixing with the curing component. Cured epoxy resin products are waste that requires no particular supervision and can as a rule be disposed of as commercial waste that is similar to household rubbish.

European waste catalogue

Possible waste code. The concrete waste code depends on the source of the waste.

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP4	Irritant - skin irritation and eye damage
HP13	Sensitising
HP14	Ecotoxic

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

EU

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 29.12.2021

Version number 1

Revision: 22.08.2019

Trade name weber.rep ep grout - component A

(Contd. of page 8)

SECTION 14: Transport information
14.1 UN number or ID number
ADR, IMDG, IATA

UN3082

14.2 UN proper shipping name
ADR

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin, Epoxy resin)

IMDG

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin, Epoxy resin), MARINE POLLUTANT

IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin, Epoxy resin)

14.3 Transport hazard class(es)
ADR

Class

9 (M6) Miscellaneous dangerous substances and articles.

Label

9

IMDG, IATA

Class

9 Miscellaneous dangerous substances and articles.

Label

9

14.4 Packing group
ADR, IMDG, IATA

III

14.5 Environmental hazards:

Product contains environmentally hazardous substances: Epoxy Resin, Epoxy resin

Marine pollutant:

Yes

Special marking (ADR):

Symbol (fish and tree)

Special marking (IATA):

Symbol (fish and tree)

Symbol (fish and tree)

14.6 Special precautions for user

Warning: Miscellaneous dangerous substances and articles.

Hazard identification number (Kemler code):

90

EMS Number:

F-A,S-F

Stowage Category

A

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Transport/Additional information:

Not dangerous according to the above specifications.

(Contd. on page 10)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 29.12.2021

Version number 1

Revision: 22.08.2019

Trade name weber.rep ep grout - component A

(Contd. of page 9)

ADR

Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000

ml

Transport category

3

IMDG

Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000

ml

UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS
SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN,
EPOXY RESIN), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Directive 2004/42/CE (VOC), cf. section 9

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 29.12.2021

Version number 1

Revision: 22.08.2019

Trade name weber.rep ep grout - component A

(Contd. of page 10)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Department issuing SDS: Research and development**Contact:**

Elif Saraçoğlu

(Certificate No:TÜV/01.260.01 - Validity date 24.12.2023)

Barış Yıldırım

(Certificate No: TÜV/01.275.01 - Validity date 25.03.2024)

Sesil Genç

(Certificate No: TÜV/01.311.11 – Validity date 04.11.2024)

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.



This document was created with the Win2PDF "print to PDF" printer available at <http://www.win2pdf.com>

This version of Win2PDF 10 is for evaluation and non-commercial use only.

This page will not be added after purchasing Win2PDF.

<http://www.win2pdf.com/purchase/>