

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.07.2023

Version number 7 (replaces version 6)

Revision: 08.03.2023

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name weberdry PUR B2K\_Component A

Safety data sheet no.: XXP013996-a

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

The product is intended for industrial or professional use.

**Application of the substance / the mixture** Polyurethane Waterproofing Coating

**Uses advised against** Uses other than those recommended.

**1.3 Details of the supplier of the safety data sheet**

**Manufacturer/Supplier:**

Saint-Gobain Weber Yapı Kim. San. ve Tic. A.S.  
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284  
35730 Kemalpaşa / Izmir  
TURKEY

Tel: +90 232 397 07 00

Fax: +90 232 397 08 00

**1.4 Emergency telephone number:**

Tel: +90 232 397 07 13-07 84

National Poison Information Center (UZEM): 114

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3      H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2      H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1      H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2      H315 Causes skin irritation.

Eye Irrit. 2      H319 Causes serious eye irritation.

Aquatic Chronic 3      H412 Harmful to aquatic life with long lasting effects.

**2.2 Label elements**

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 11.07.2023

Version number 7 (replaces version 6)

Revision: 08.03.2023

**Trade name weberdry PUR B2K\_Component A**

(Contd. of page 1)

### Hazard pictograms



GHS02 GHS07 GHS08

**Signal word** Danger

### Hazard-determining components of labelling:

reaction mass of ethylbenzene and xylene

reaction mass of ethylbenzene and m-xylene and p-xylene

### Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P331 Do NOT induce vomiting.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### Additional information:

As from 24 August 2023 adequate training is required before industrial or professional use.

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

**Description:** Mixture consisting of the following components.

<b>Dangerous components:</b>		
CAS: 8052-42-4 EINECS: 232-490-9 Reg.nr.: 01-2119480172-44-xxxx	Asphalt substance with a Community workplace exposure limit	≥70-<80%
EC number: 905-588-0 Reg.nr.: 01-2119486136-34-xxxx	reaction mass of ethylbenzene and xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Specific concentration limit: STOT RE 2; H373: C ≥ 10 %	≥10-≤15%

(Contd. on page 3)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.07.2023

Version number 7 (replaces version 6)

Revision: 08.03.2023

**Trade name weberdry PUR B2K\_Component A**

(Contd. of page 2)

EC number: 905-562-9 Reg.nr.: 01-2119488216-32-xxxx	reaction mass of ethylbenzene and m-xylene and p-xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412 Specific concentration limit: STOT RE 2; H373: C ≥ 10 %	≥2.5-<10%
CAS: 5285-60-9 EINECS: 226-122-6 Reg.nr.: 01-2120807289-49-xxxx	4,4'-methylenebis[N-sec-butylaniline] ⚠ Acute Tox. 4, H302	≥2.5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	≥1-<2.5%
CAS: 68479-98-1 EINECS: 270-877-4 Index number: 612-130-00-0 Reg.nr.: 01-2119486805-25-xxxx	diethylmethylbenzenediamine ⚠ STOT RE 2, H373; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Eye Irrit. 2, H319	≥0.25-<1%

**SVHC** Void

**Additional information** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**General information**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

Seek immediate medical advice

Immediately remove any clothing soiled by the product.

**After inhalation**

Supply fresh air and to be sure call for a doctor.

Seek medical treatment in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact**

Rinse opened eye for several minutes under running water. Rinse liquid should be tempered (20-30°C).

Seek immediate medical advice.

**After swallowing**

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Seek immediate medical advice.

(Contd. on page 4)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 11.07.2023

Version number 7 (replaces version 6)

Revision: 08.03.2023

**Trade name weberdry PUR B2K\_Component A**

(Contd. of page 3)

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray.**For safety reasons unsuitable extinguishing agents** Water with full jet**5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

**5.3 Advice for firefighters****Protective equipment:**

Wear fully protective suit.

Wear self-contained respiratory protective device.

**Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

Use respiratory protective device against the effects of fumes/dust/aerosol.

Avoid inhalation of vapors.

**6.2 Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

**6.3 Methods and material for containment and cleaning up:**

Absorb liquid components with liquid-binding material.

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb with sawdust or other combustible absorbents.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents.

**6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin and eyes.

Do not breath vapours.

(Contd. on page 5)

EUG

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.07.2023

Version number 7 (replaces version 6)

Revision: 08.03.2023

**Trade name weberdry PUR B2K\_Component A**

(Contd. of page 4)

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage**

**Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Prevent any seepage into the ground.

Provide ventilation for receptacles.

Store away from sources of ignition.

**Information about storage in one common storage facility:** Store away from foodstuffs.

**Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

**7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

**DNELs**

**reaction mass of ethylbenzene and m-xylene and p-xylene**

Oral	Derived No Effect Level	1.6 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	180 mg/kgxday (worker systemic long term value) 125 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	77 mg/m <sup>3</sup> (worker systemic long term value) 442 mg/m <sup>3</sup> (worker systemic short term value) 15 mg/m <sup>3</sup> (consumer systemic long term value) 260 mg/m <sup>3</sup> (consumer systemic short term value)

**CAS: 68479-98-1 diethylmethylenediamine**

Dermal	Derived No Effect Level	1 mg/kgxday (worker systemic long term value) 1 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	0.13 mg/m <sup>3</sup> (worker systemic long term value) 0.1 mg/m <sup>3</sup> (consumer systemic long term value)

**PNECs**

**reaction mass of ethylbenzene and m-xylene and p-xylene**

Predicted No-Effect Concentration	0.852 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration	0.0044 mg/l (sea water rating factor) 0.044 mg/l (fresh water rating factor)

(Contd. on page 6)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 11.07.2023

Version number 7 (replaces version 6)

Revision: 08.03.2023

**Trade name weberdry PUR B2K\_Component A**

(Contd. of page 5)

CAS No. / Designation of material / % / Type / Value / Unit	
<b>CAS: 8052-42-4 Asphalt</b>	
MAK (Germany)	Long-term value: 1.5 mg/m <sup>3</sup> Dampf und Aerosol
GV (Denmark)	Long-term value: 1 mg/m <sup>3</sup>
LEP (Spain)	Long-term value: 0.5 mg/m <sup>3</sup> aerosoles solubles en benceno
TWA (Italy)	Long-term value: 0.5 mg/m <sup>3</sup> A4 , IBEp, (i)
VLE (Portugal)	Long-term value: 0.5 mg/m <sup>3</sup> Fração inal.; A4, IBEp; Irritação ocular e do TRS
<b>CAS: 123-86-4 n-butyl acetate</b>	
IOELV (European Union)	Short-term value: 723 mg/m <sup>3</sup> , 150 ppm Long-term value: 241 mg/m <sup>3</sup> , 50 ppm
AGW (Germany)	Long-term value: 300 mg/m <sup>3</sup> , 62 ppm 2(I);AGS, Y
GV (Denmark)	Short-term value: 723 mg/m <sup>3</sup> , 150 ppm Long-term value: 241 mg/m <sup>3</sup> , 50 ppm E
LEP (Spain)	Short-term value: 723 mg/m <sup>3</sup> , 150 ppm Long-term value: 241 mg/m <sup>3</sup> , 50 ppm VLI
TWA (Italy)	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 713 mg/m <sup>3</sup> , 150 ppm
VL (Italy)	Short-term value: 723 mg/m <sup>3</sup> , 150 ppm Long-term value: 241 mg/m <sup>3</sup> , 50 ppm
VLE (Portugal)	Short-term value: 200 ppm Long-term value: 150 ppm Irritação ocular e do TRS
OEL (Sweden)	Short-term value: 723 mg/m <sup>3</sup> , 150 ppm Long-term value: 241 mg/m <sup>3</sup> , 50 ppm
HTP (Finland)	Short-term value: 725 mg/m <sup>3</sup> , 150 ppm Long-term value: 240 mg/m <sup>3</sup> , 50 ppm

### 8.2 Exposure controls

**Appropriate engineering controls** No further data; see section 7.

**Individual protection measures, such as personal protective equipment**

**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Do not eat, drink, smoke or sniff while working.

Do not inhale dust / smoke / mist.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Ensure adequate ventilation during use.

(Contd. on page 7)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.07.2023

Version number 7 (replaces version 6)

Revision: 08.03.2023

**Trade name weberdry PUR B2K\_Component A**

(Contd. of page 6)

**Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.  
Respiratory protection required in insufficiently ventilated working areas and during spraying.  
In case of brief exposure or low pollution use respiratory filter device.  
In case of intensive or longer exposure use self-contained respiratory protective device.  
Short term filter device:  
Combination of charcoal filter and particulate filter A2-P2 (EN 529)

**Hand protection**

Protective gloves against chemicals (standard EN 374-1)  
The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.  
Due to missing tests no recommendation to the glove material can be given for the product/ the mixture/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.  
Recommendation: contaminated gloves should be disposed of.

Butyl rubber, BR

Fluorocarbon rubber (FKM-Viton)

Recommended thickness of the material:  $\geq 0.5$ (BR); 0.4 (Viton) mm

**Penetration time of glove material**

The determined breakthrough times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the breakthrough time, is recommended.

For the mixture of chemicals mentioned below the breakthrough time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

**Eye/face protection**

Tightly sealed goggles  
Protective eyewear (standard EN 166)

**Body protection:**

Chemically resistant protective work clothing (EN 14605)  
Boots

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

<b>Colour:</b>	Black
<b>Odour:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.
<b>Melting point/freezing point:</b>	Undetermined.
<b>Boiling point or initial boiling point and boiling range</b>	130-150 °C (EC No. 905-588-0)
<b>Flammability</b>	Not applicable.

(Contd. on page 8)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 11.07.2023

Version number 7 (replaces version 6)

Revision: 08.03.2023

**Trade name weberdry PUR B2K\_Component A**

(Contd. of page 7)

**Lower and upper explosion limit**

<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
<b>Flash point:</b>	34 °C (Pensky-Marten)
<b>Auto-ignition temperature:</b>	488 °C (EC No. 905-588-0)
<b>Decomposition temperature:</b>	Not determined.
<b>pH</b>	Not applicable.
<b>Viscosity:</b>	
<b>Kinematic viscosity at 23 °C</b>	520 s (ISO 2431/Flow time tISO)
<b>dynamic:</b>	Not determined.
<b>Solubility</b>	
<b>Water:</b>	Not determined.
<b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
<b>Vapour pressure:</b>	Not determined.
<b>Density and/or relative density</b>	
<b>Density at 20 °C:</b>	0.98 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined.
<b>Bulk density:</b>	Not applicable.
<b>Vapour density</b>	Not determined.

**9.2 Other information**

<b>Appearance:</b>	
<b>Form:</b>	Viscous
<b>Important information on protection of health and environment, and on safety.</b>	
<b>Ignition temperature:</b>	Product is not self-igniting.
<b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<b>Minimum ignition energy</b>	
<b>Solvent separation test:</b>	<1 % (UN Part III, par. 32.5.1)
<b>EU-VOC (g/L)</b>	170.0000 g/l
<b>Change in condition</b>	
<b>Softening point/range</b>	
<b>Oxidising properties</b>	Not considered as oxidising.
<b>Evaporation rate</b>	Not determined.

**Information with regard to physical hazard classes**

<b>Explosives</b>	Void
<b>Flammable gases</b>	Void
<b>Aerosols</b>	Void
<b>Oxidising gases</b>	Void
<b>Gases under pressure</b>	Void
<b>Flammable liquids</b>	Flammable liquid and vapour.
<b>Flammable solids</b>	Void
<b>Self-reactive substances and mixtures</b>	Void
<b>Pyrophoric liquids</b>	Void
<b>Pyrophoric solids</b>	Void

(Contd. on page 9)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 11.07.2023

Version number 7 (replaces version 6)

Revision: 08.03.2023

Trade name weberdry PUR B2K\_Component A

(Contd. of page 8)

Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

### SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

**10.2 Chemical stability** Stable at recommended storage conditions

**Thermal decomposition / Conditions to be avoided:** Stable at environment temperature.

**10.3 Possibility of hazardous reactions** No dangerous reactions known

**10.4 Conditions to avoid** Avoid heat, sparkles, naked flame or other sources of ignition.

**10.5 Incompatible materials:** Oxydising agents.

**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:**

Components	Type	Value	Species
Oral	LD50	13,596 mg/kg	(Calculation)
Dermal	LD50	5,856 mg/kg	(Calculation)
Inhalative	LC50/4 h	61.8 mg/l	(Calculation)

**CAS: 8052-42-4 Asphalt**

Oral	LD50	>5,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rabbit)

**reaction mass of ethylbenzene and xylene**

Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rabbit)
Inhalative	LC50/4 h	>20 mg/l	(Rat)

**reaction mass of ethylbenzene and m-xylene and p-xylene**

Oral	LD50	>3,523 mg/kg	(Rat)
Dermal	LD50	>12,126 mg/kg	(Rabbit)
Inhalative	LC50/4 h	>27 mg/l	(Rat)

**CAS: 5285-60-9 4,4'-methylenebis[N-sec-butylaniline]**

Oral	LD50	>300 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)

(Contd. on page 10)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 11.07.2023

Version number 7 (replaces version 6)

Revision: 08.03.2023

Trade name weberdry PUR B2K\_Component A

(Contd. of page 9)

**CAS: 123-86-4 n-butyl acetate**

Oral	LD50	14,000 mg/kg (Rat)
Inhalative	LC50/4 h	>21 mg/l (Rat)

**CAS: 68479-98-1 diethylmethylenediamine**

Oral	LD50	738 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rat)

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/irritation** Causes serious eye irritation.**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**11.2 Information on other hazards****Endocrine disrupting properties**

None of the ingredients is listed.

## SECTION 12: Ecological information

**12.1 Toxicity****Aquatic toxicity:** Harmful to aquatic life with long lasting effects.**Type of test / Effective concentration / Method / Assessment****reaction mass of ethylbenzene and xylene**

LC50/96h	2.6 mg/l (Fish)
EC50/24h	1 mg/l (Daphnia magna)
EC50/72h	1.3 mg/l (Algae)
NOEC (21d)	1.57 mg/l (Daphnia magna)
EC 10	1.3 mg/l (Fish)

**reaction mass of ethylbenzene and m-xylene and p-xylene**

LC50/48h	10.389 mg/l (Daphnia magna)
LC50/96h	>2.6 mg/l (Fish)
EC50/24h	96 mg/l (Activated sludge)
EC50/72h	4.6-4.9 mg/l (Algae)
NOEC (21d)	1.57 mg/l (Daphnia magna)

**CAS: 5285-60-9 4,4'-methylenedibis[N-sec-butylaniline]**

LC50/96h	0.61 mg/l (Fish)
EC50/48h	0.21 mg/l (Daphnia magna)

(Contd. on page 11)

EUG

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 11.07.2023

Version number 7 (replaces version 6)

Revision: 08.03.2023

**Trade name weberdry PUR B2K\_Component A**

(Contd. of page 10)

EC50/72h	0.187 mg/l (Algae)
<b>CAS: 123-86-4 n-butyl acetate</b>	
LC50/48h	64 mg/l (Brachydanio rerio (zebra danio))
EC50/72h	674 mg/l (Scenedesmus subspicatus (Algae))
EC 10	959 mg/l (Pseudomonas putida (Bacteria))
<b>CAS: 68479-98-1 diethylmethylbenzenediamine</b>	
LC50/48h	200 mg/l (Fish)
EC50/48h	0.5 mg/l (Daphnia magna)

**12.2 Persistence and degradability** No further relevant information available.

**Method**

**reaction mass of ethylbenzene and xylene**

Biod. (28 days) | 75 % (Biodegradation)

**Behaviour in environmental systems:**

**Components:**

**reaction mass of ethylbenzene and m-xylene and p-xylene**

DT50-value (Degradation Half Time) | 2 day

**12.3 Bioaccumulative potential**

**reaction mass of ethylbenzene and m-xylene and p-xylene**

EBAB | 3.16-3.6 log Pow

**12.4 Mobility in soil** No further relevant information available.

**12.5 Results of PBT and vPvB assessment**

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**12.7 Other adverse effects**

**Remark:** Harmful to fish

**Behaviour in sewage processing plants:**

**Type of test / Effective concentration / Method / Assessment**

**CAS: 5285-60-9 4,4'-methylenebis[N-sec-butylaniline]**

EC 50 (3h) | 1,000 mg/l (Activated sludge)

**Additional ecological information:**

**General notes:**

The product contains materials that are harmful to the environment.

Harmful to aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

### SECTION 13: Disposal considerations

**13.1 Waste treatment methods**

**Recommendation**

Dispose of the product in accordance with national and local regulations.

(Contd. on page 12)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 11.07.2023

Version number 7 (replaces version 6)

Revision: 08.03.2023

**Trade name weberdry PUR B2K\_Component A**

(Contd. of page 11)

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP14	Ecotoxic

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

**14.1 UN number or ID number**  
ADR, IMDG, IATA

UN1866

**14.2 UN proper shipping name**  
ADR  
IMDG, IATA

1866 RESIN SOLUTION  
RESIN SOLUTION

**14.3 Transport hazard class(es)**

ADR



**Class**  
**Label**

3 (F1) Flammable liquids.  
3

-----  
IMDG, IATA



**Class**  
**Label**

3 Flammable liquids.  
3

**14.4 Packing group**  
ADR, IMDG, IATA

III

**14.5 Environmental hazards:**

Not applicable.

**14.6 Special precautions for user**  
**Hazard identification number (Kemler code):** 30  
**EMS Number:**  
**Stowage Category**

Warning: Flammable liquids.  
F-E, S-E  
A

**14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

(Contd. on page 13)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 11.07.2023

Version number 7 (replaces version 6)

Revision: 08.03.2023

**Trade name weberdry PUR B2K\_Component A**

(Contd. of page 12)

**Transport/Additional information:**

**ADR**

Limited quantities (LQ)  
Excepted quantities (EQ)

5L  
Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

Transport category  
Tunnel restriction code

3  
D/E

**Remarks:**

Not subject to ADR Class 3 if packaging ≤ 5L according to ADR 2.2.3.1.5.2

**IMDG**

Limited quantities (LQ)  
Excepted quantities (EQ)

5L  
Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

**Remarks:**

Not subject to IMDG Class 3 if packaging ≤ 5L according to IMDG 2.3.2.5.

**UN "Model Regulation":**

UN 1866 RESIN SOLUTION, 3, III

### SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Directive 2004/42/EC (VOC), cf. section 9

**Labelling according to Regulation (EC) No 1272/2008** cf. section 2

**Directive 2004/42/EC**

Product type: PAINTS AND VARNISHES

- Product subcategory: One-pack performance coatings
- Solvent-borne coatings, Limit value: 500 g/l

VOC: 170.0000 g/l

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category** P5c FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

**DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

(Contd. on page 14)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.07.2023

Version number 7 (replaces version 6)

Revision: 08.03.2023

**Trade name weberdry PUR B2K\_Component A**

(Contd. of page 13)

**REGULATION (EU) 2019/1148**

**Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

**Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

**Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

**Relevant phrases**

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 15)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 11.07.2023

Version number 7 (replaces version 6)

Revision: 08.03.2023

**Trade name weberdry PUR B2K\_Component A**

(Contd. of page 14)

Classification according to Regulation (EC) No 1272/2008	
Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
Aspiration hazard	Expert judgement

**Department issuing SDS:** Research and development

**Contact:**

Necati Utku Erol  
(Sertifika No:TÜV/01.336.07 - Validity date 31.12.2023)

Barış Yıldırım  
(Sertifika No: TÜV/01.275.01 - Validity date 25.03.2024)

Sesil Genç  
(Sertifika No: TÜV/01.311.11 – Validity date 04.11.2024)

**Date of previous version:** 01.03.2022

**Version number of previous version:** 6

**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**\* Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.