

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **weberprim 500 F-a**

Safety data sheet no.: XXP01811-a

1.2 Relevant identified uses of the substance or mixture and uses advised against

The product is intended for professional or consumer use.

Application of the substance / the mixture Epoxy resin

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Weber Yapı Kim. San. ve Tic. A.S.
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284
35730 Kemalpaşa / Izmir
TURKEY

Tel: +90 232 397 07 00

Fax: +90 232 397 08 00

1.4 Emergency telephone number:

Tel: +90 232 397 07 13-07 84

National Poison Information Center (UZEM): 114

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Repr. 1B

H360F May damage fertility.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

EUG

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 1)

Hazard pictograms



GHS07 GHS08 GHS09

Signal word Danger

Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) oxirane, mono[(C12-14-alkyloxy)methyl] derivs

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Restricted to professional users.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

The product contains silica sand with less than 1% of fine fraction and therefore is not classified as hazardous; however, pay attention when handling and follow the indications relating to personal protective equipment.

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

Determination of endocrine-disrupting properties

Does not contain substances with endocrine-disrupting properties.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with non hazardous additions.

(Contd. on page 3)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 2)

Dangerous components:		
CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	25-50%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-xxxx	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5% Eye Irrit. 2; H319: C ≥ 5 %	25-50%
CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26-xxxx	2, 2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5% Eye Irrit. 2; H319: C ≥ 5 %	5-10%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22-xxxx	oxirane, mono[(C12-14-alkyloxy)methyl] derivs ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	≥5-<10%
EC number: 701-263-0 Reg.nr.: 01-2119454392-40-xxxx	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane Alternative CAS number: 9003-36-5 ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<5%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-xxxx	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	2-5%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22-xxxx	oxirane, mono[(C12-14-alkyloxy)methyl] derivs ⚠ Repr. 1B, H360F; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	2-5%
CAS: 398475-96-2 EC number: 812-737-2	1,2-Ethanediamine, polymer with aziridine, N-[3-[(2-ethylhexyl)oxy]-3-oxopropyl] derivs., compds. with polyethylene-polypropylene glycol mono-Bu ether phosphate ⚠ Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1); ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	≥0.25-<1%

SVHC Void

(Contd. on page 4)

EUG

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 3)

Additional information

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 1%. The respirable fraction has an occupational exposure limit value (cf. section 8). For the wording of the listed hazard statements refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.
Never administer anything by mouth to an unconscious person.
If unconscious, place the patient in a stable side position and consult a doctor

After inhalation

In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air and to be sure call for a doctor.

After skin contact

Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
Rinse liquid should be tempered (20-30°C).

After swallowing Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Use fire extinguishing methods suitable to surrounding conditions.
The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire. Use foam, carbon dioxide, dry powder or water fog to extinguish.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

Use methods suitable to surrounding conditions.
Wear fully protective suit.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

EUG

(Contd. on page 5)

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 4)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Ensure adequate ventilation.

6.2 Environmental precautions:

The product must not get into watercourses or into the soil.

Inform respective authorities in case of seepage into water course or sewage system.

Do not drain into drains or public waters. Alert the relevant authorities if the liquid enters a sewer or open water enters.

Suppress gases/fumes/haze with water spray.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water.

7.3 Specific end use(s) No further relevant information available.

EUG

(Contd. on page 6)

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 5)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs		
CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)		
Oral	Derived No Effect Level	0.75 mg/kgxday (consumer systemic long term value) 0.75 mg/kgxday (consumer systemic short term value)
Dermal	Derived No Effect Level	8.33 mg/kgxday (worker systemic long term value) 8.33 mg/kgxday (worker systemic short term value) 3.571 mg/kgxday (consumer systemic long term value) 3.571 mg/kgxday (consumer systemic short term value)
Inhalative	Derived No Effect Level	12.3 mg/m ³ (worker systemic long term value) 12.3 mg/m ³ (worker systemic short term value)
CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane		
Oral	Derived No Effect Level	0.5 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	0.75 mg/kgxday (worker systemic long term value) 0.0893 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	4.93 mg/m ³ (worker systemic long term value) 0.87 mg/m ³ (consumer systemic long term value)
CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs		
Oral	Derived No Effect Level	0.05 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	0.75 mg/kgxday (worker systemic long term value) 0.089 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	0.49 mg/m ³ (worker systemic long term value) 0.087 mg/m ³ (consumer systemic long term value)
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane		
Oral	Derived No Effect Level	6.25 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	104.15 mg/kgxday (worker systemic long term value) 6.25 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	29.39 mg/m ³ (worker systemic long term value) 8.7 mg/m ³ (consumer systemic long term value)
CAS: 100-51-6 Benzyl alcohol		
Oral	Derived No Effect Level	4 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	8 mg/kgxday (worker systemic long term value) 4 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	22 mg/m ³ (worker systemic long term value)

(Contd. on page 7)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 6)

		5.4 mg/m ³ (consumer systemic long term value)
CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs		
Oral	Derived No Effect Level	0.05 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	0.75 mg/kgxday (worker systemic long term value)
		0.089 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	0.49 mg/m ³ (worker systemic long term value)
		0.087 mg/m ³ (consumer systemic long term value)

PNECs

CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Predicted No-Effect Concentration	0.065 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration	0.0006 mg/l (sea water rating factor)
	0.006 mg/l (fresh water rating factor)

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Predicted No-Effect Concentration	20 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration	0.112 mg/l (sea water rating factor)
	1.12 mg/l (fresh water rating factor)

CAS: 100-51-6 Benzyl alcohol

Predicted No-Effect Concentration	0.456 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration	0.1 mg/l (sea water rating factor)
	1 mg/l (fresh water rating factor)

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Predicted No-Effect Concentration	20 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration	0.112 mg/l (sea water rating factor)
	1.12 mg/l (fresh water rating factor)

CAS No. / Designation of material / % / Type / Value / Unit

CAS: 14808-60-7 Silicon dioxide (Quartz sand)

BOELV (European Union)	Long-term value: 0.1* mg/m ³ *respirable fraction
MAK (Germany)	alveolengängige Fraktion
GV (Denmark)	Short-term value: 0.6* 0.2** mg/m ³ Long-term value: 0.3* 0.1** mg/m ³ *total; **total, respirabel: EK
LEP (Spain)	Long-term value: 0.05 mg/m ³ *Fracción resp:n,d,y
TWA (Italy)	Long-term value: 0.025 mg/m ³ A2, (j)
VLE (Portugal)	Long-term value: 0.025 mg/m ³ Resp.;A2; fibrose pulmonar; cancro do pulmão
OEL (Sweden)	Long-term value: 0.1 mg/m ³ C, M, respirabel fraktion

(Contd. on page 8)

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 7)

HTP (Finland)	Long-term value: 0.05 0.1* mg/m ³ alveolijae;*sitovat raja-arvot, pöly
CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	
MAK (Germany)	vgl. Abschn. IIb
CAS: 100-51-6 Benzyl alcohol	
AGW (Germany)	Long-term value: 22 mg/m ³ , 5 ppm 2(I);DFG, H, Y, 11
HTP (Finland)	Long-term value: 45 mg/m ³ , 10 ppm

Additional Occupational Exposure Limit Values for possible hazards during processing:

Total inhalable dust: 10 mg/m³ ; Respirable dust: 1 mg/m³

UK and Ireland: Total inhalable dust: 10 mg/m³ ; Respirable dust: 4 mg/m³

Quartz respirable dust:

European Union: 0,1mg/m³

UK: 0,1 mg/m³

Ireland: 0,1 mg/m³

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Use a moisturising skin cream after processing the product.

Respiratory protection:

Short term filter device:

Filter P2.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection Protective gloves.

Material of gloves Nitrile impregnated cotton gloves complying with the standard EN 374-1.

For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Nitrile rubber, NBR

Eye/face protection Safety glasses.

Body protection: Protective work clothing.

EUG

(Contd. on page 9)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 8)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Fluid
Colour:	Yellowish
Odour:	Aromatic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	>200 °C (DIN, CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	1.3 Vol % (DIN 51649, CAS: 100-51-6 Benzyl alcohol)
Upper:	13 Vol % (DIN 51649, CAS: 100-51-6 Benzyl alcohol)
Flash point:	93 °C (DIN ISO 2592, Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane)
Auto-ignition temperature:	184 °C (DIN 51794, CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))
Decomposition temperature:	Not determined.
pH	Mixture reacts violently with water.
Viscosity:	
Kinematic viscosity	Not determined.
dynamic:	Not determined.
Solubility	
Water:	Emulsifiable
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	<0.1 hPa (DIN 51640, CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))
Density and/or relative density	
Density:	Not determined
Relative density	Not determined.
Bulk density:	Not applicable.
Vapour density	Not determined.

(Contd. on page 10)

EUG

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 9)

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and environment, and on safety.

Ignition temperature: Product is not self-igniting.

Explosive properties: Product does not present an explosion hazard.

Minimum ignition energy

Solvent separation test: Not applicable.

Solvent content:

Organic solvents: 10.7 %

EU-VOC (%): 2.9980 %

EU-VOC (g/L): 29.9800 g/l

Solids content: >50.7-≤50.8 %

Change in condition

Softening point/range

Oxidising properties: Not determined.

Evaporation rate: Not determined.

Information with regard to physical hazard classes

Explosives: Void

Flammable gases: Void

Aerosols: Void

Oxidising gases: Void

Gases under pressure: Void

Flammable liquids: Void

Flammable solids: Void

Self-reactive substances and mixtures: Void

Pyrophoric liquids: Void

Pyrophoric solids: Void

Self-heating substances and mixtures: Void

Substances and mixtures, which emit flammable gases in contact with water: Void

Oxidising liquids: Void

Oxidising solids: Void

Organic peroxides: Void

Corrosive to metals: Void

Desensitised explosives: Void

SECTION 10: Stability and reactivity

10.1 Reactivity: Not reactive under normal conditions of use

10.2 Chemical stability: Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

(Contd. on page 11)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 10)

10.3 Possibility of hazardous reactions Reacts with acids

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)			
Oral	LD50	>5,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rabbit)
CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane			
Oral	LD50	>15,000 mg/kg	(Rat)
Dermal	LD50	>23,000 mg/kg	(Rat)
CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>4,000 mg/kg	(Rabbit)
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane			
Oral	LD50	>5,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)
CAS: 100-51-6 Benzyl alcohol			
Oral	LD50	1,620 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rabbit)
Inhalative	LC50/4 h	>4.178 mg/l	(Rat)
CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>4,000 mg/kg	(Rabbit)

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity May damage fertility.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 12)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 11)

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Toxic to aquatic life with long lasting effects (H411)

Toxic to aquatic life with long lasting effects.

Type of test / Effective concentration / Method / Assessment

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

LC50/96h	2 mg/l (Leuciscus idus (Orfe)) 1.3 mg/l (Fish)
EC50/24h	4.6 mg/l (Daphnia magna)
EC50/48h	1.8 mg/l (Daphnia magna)
EC50/96h	220 mg/l (Selenastrum capricornutum (Green algae))
NOEC (21d)	0.3 mg/l (Daphnia magna)

CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

LC50/96h	2 mg/l (Fish)
EC50/48h	1.8 mg/l (Daphnia magna)
EC50/72h	>11 mg/l (Algae)
NOEC (72h)	4.2 mg/l (Algae)
NOEC (21d)	0.3 mg/l (Daphnia magna)

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

IC50/72h	843.75 mg/l (aquatic algae and cyanobacteria)
LC50/96h	>100 mg/l (Fish)
EC50/48h	7.2 mg/l (aquatic invertebrates)
EC50/72h	843.75 mg/l (aquatic algae and cyanobacteria)
NOEC (72h)	500 mg/l (aquatic algae and cyanobacteria)
NOEC (21d)	56 mg/l (aquatic invertebrates)
NOEC (28d)	100 mg/l (microorganisms)

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

LC50/48h	2.55 mg/l (Fish)
EC50/48h	1.6-3.5 mg/l (Daphnia magna)
EC50/72h	1.8 mg/l (Algae)
NOEC (21d)	0.3 mg/l (Daphnia magna)

(Contd. on page 13)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 12)

CAS: 100-51-6 Benzyl alcohol

LC50/96h	>100 mg/l (Fish)
EC50/24h	400 mg/l (aquatic invertebrates)
EC50/48h	230 mg/l (aquatic invertebrates)
EC50/72h	759 mg/l (aquatic algae and cyanobacteria)
NOEC (72h)	556 mg/l (aquatic algae and cyanobacteria)
NOEC (48h)	171 mg/l (aquatic invertebrates)
NOEC (21d)	51 mg/l (aquatic invertebrates)
EC 10/16h	658 mg/l (microorganisms)

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

IC50/72h	843.75 mg/l (aquatic algae and cyanobacteria)
LC50/96h	>100 mg/l (Fish)
EC50/48h	7.2 mg/l (aquatic invertebrates)
EC50/72h	843.75 mg/l (aquatic algae and cyanobacteria)
NOEC (72h)	500 mg/l (aquatic algae and cyanobacteria)
NOEC (21d)	56 mg/l (aquatic invertebrates)
NOEC (28d)	100 mg/l (microorganisms)

12.2 Persistence and degradability No further relevant information available.

Method

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Biod. (28 days) >80 %

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Biod. (28 days) >80 %

12.3 Bioaccumulative potential

CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

EBAB 3.242 log Pow

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

EBAB 3.77 log Pow (-)

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

EBAB 3.6 log Pow (Bioaccumulation)

CAS: 100-51-6 Benzyl alcohol

EBAB 1.05 log Pow (Bioaccumulation)

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

EBAB 3.77 log Pow (-)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

(Contd. on page 14)

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 13)

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark:

The product contains substances which are toxic to fishes and bacteria.
Toxic for fish

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment	
CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	
EC 50 (3h)	100 mg/l (microorganisms)
CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs	
EC 50 (3h)	100 mg/l (microorganisms)
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane	
EC 50 (3h)	100 mg/l (Activated sludge)
CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs	
EC 50 (3h)	100 mg/l (microorganisms)

Additional ecological information:

General notes:

Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Dispose of the product in accordance with national and local regulations.

European waste catalogue	
08 04 11*	adhesive and sealant sludges containing organic solvents or other hazardous substances
08 04 99	wastes not otherwise specified
HP4	Irritant - skin irritation and eye damage
HP10	Toxic for reproduction
HP13	Sensitising
HP14	Ecotoxic

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleaning agent: Water, if necessary together with cleansing agents.

EUG

(Contd. on page 15)

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 14)

SECTION 14: Transport information

14.1 UN number or ID number
ADR, IMDG, IATA

UN3082

14.2 UN proper shipping name
ADR

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin, Epoxy resin)

IMDG

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin, Epoxy resin), MARINE POLLUTANT

IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin, Epoxy resin)

14.3 Transport hazard class(es)

ADR




Class

9 (M6) Miscellaneous dangerous substances and articles.

Label

9

IMDG, IATA



Class

9 Miscellaneous dangerous substances and articles.

Label

9

14.4 Packing group
ADR, IMDG, IATA

III

14.5 Environmental hazards:

Product contains environmentally hazardous substances: Epoxy Resin

Marine pollutant:

Symbol (fish and tree)

Special marking (ADR):

Symbol (fish and tree)

Special marking (IATA):

Symbol (fish and tree)

14.6 Special precautions for user

Warning: Miscellaneous dangerous substances and articles.

Hazard identification number (Kemler code):

90

EMS Number:

F-A,S-F

Stowage Category

A

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

(Contd. on page 16)

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 15)

Transport/Additional information:

ADR

Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport category

3

Tunnel restriction code

(-)

IMDG

Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS
SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN,
EPOXY RESIN), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 17)

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 16)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H360F May damage fertility.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH205 Contains epoxy constituents. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Reproductive toxicity Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--	--

Department issuing SDS: Research and development

Contact:

Necati Utku Erol
(Sertifika No:TÜV/01.336.07 - Validity date 31.12.2023)

Barış Yıldırım
(Sertifika No: TÜV/01.275.01 - Validity date 25.03.2024)

Sesil Genç
(Sertifika No: TÜV/01.311.11 – Validity date 04.11.2024)

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 18)

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2024

Version number 1

Revision: 21.05.2024

Trade name: weberprim 500 F-a

(Contd. of page 17)

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern (REACH regulation)
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 1B: Reproductive toxicity – Category 1B
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

EUG



This document was created with the Win2PDF "print to PDF" printer available at <http://www.win2pdf.com>

This version of Win2PDF 10 is for evaluation and non-commercial use only.

This page will not be added after purchasing Win2PDF.

<http://www.win2pdf.com/purchase/>