

**Safety Data Sheet**  
according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 19.08.2025

Version number 1

Revision: 26.10.2022

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name: weberkol flex dinamik

Safety data sheet no.: XXP017159

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

**Application of the substance / the mixture** Tile adhesive

**1.3 Details of the supplier of the safety data sheet**

**Manufacturer/Supplier:**

Saint-Gobain Weber Yapı Kim. San. ve Tic. A.S.  
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284  
35730 Kemalpaşa / Izmir  
TURKEY

Tel: +90 232 397 07 00

Fax: +90 232 397 08 00

**1.4 Emergency telephone number:**

Tel: +90 232 397 07 13-07 84

National Poison Information Center (UZEM): 114

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008**

Results of in vitro- tests have shown that cement based mixtures with more than 1% of cement cause serious skin irritation and serious eye damage, therefore the classification of these mixtures regarding H315 and H318 is not based on the calculation of the ingredients or the pH in this case.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

**2.2 Label elements**

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

EUG

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 19.08.2025

Version number 1

Revision: 26.10.2022

**Trade name: weberkol flex dinamik**

(Contd. of page 1)

### Hazard pictograms



GHS05 GHS07

**Signal word** Danger

### Hazard-determining components of labelling:

Cement, portland, chemicals

### Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

### Precautionary statements

P261 Avoid breathing dust.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

**Description:** Mixture of substances listed below with non hazardous additions.

#### Dangerous components:

CAS: 1317-65-3 EINECS: 215-279-6 Reg.nr.: 01-2119486795-18-xxxx	calcium carbonate substance with a Community workplace exposure limit	25-50%
CAS: 65997-15-1 EINECS: 266-043-4	Cement, portland, chemicals ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Skin Sens. 1B, H317; STOT SE 3, H335, EUH203 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 % substance with a Community workplace exposure limit	25-50%

**SVHC** Void

(Contd. on page 3)

**Safety Data Sheet**  
according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 19.08.2025

Version number 1

Revision: 26.10.2022

**Trade name: weberkol flex dinamik**

(Contd. of page 2)

**Additional information** For the wording of the listed hazard statements refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

Immediately remove any clothing soiled by the product.

#### After inhalation

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air and to be sure call for a doctor.

**After skin contact** Immediately wash with water and soap and rinse thoroughly.

#### After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

**After swallowing** Rinse mouth. DO NOT induce vomiting. If symptoms persist consult a doctor.

### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing agents

The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire. Use foam, carbon dioxide, dry powder or water fog to extinguish.

### 5.2 Special hazards arising from the substance or mixture

The product is not flammable, it is not explosive, and does not enable or feed combustion in other materials.

### 5.3 Advice for firefighters

#### Protective equipment:

Use methods suitable to surrounding conditions.

Wear fully protective suit.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Ensure adequate ventilation.

### 6.2 Environmental precautions:

In case of seepage into the ground inform responsible authorities.

Do not allow to enter sewers/ surface or ground water.

### 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

(Contd. on page 4)

**Safety Data Sheet**  
 according to Regulation (EC) No 1907/2006, Article 31, as amended  
 by Regulation (EU) 2020/878.

Printing date 19.08.2025

Version number 1

Revision: 26.10.2022

**Trade name: weberkol flex dinamik**

(Contd. of page 3)

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

Thorough dedusting.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of dust.

Provide suction extractors if dust is formed.

**Information about fire - and explosion protection:** No special measures required.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage**

**Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

**Information about storage in one common storage facility:** Store away from foodstuffs.

**Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water.

**7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

**DNELs**

**CAS: 1317-65-3 calcium carbonate**

Oral	Derived No Effect Level	6.1 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	6.36 mg/m <sup>3</sup> (worker local long term value)
		1.06 mg/m <sup>3</sup> (consumer local long term value)

**PNECs**

**CAS: 65996-69-2 Slags, ferrous metal, blast furnace**

Predicted No-Effect Concentration	1,000 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration	500 mg/l (sea water rating factor)
	5,000 mg/l (fresh water rating factor)

(Contd. on page 5)

**Safety Data Sheet**  
 according to Regulation (EC) No 1907/2006, Article 31, as amended  
 by Regulation (EU) 2020/878.

Printing date 19.08.2025

Version number 1

Revision: 26.10.2022

**Trade name: weberkol flex dinamik**

(Contd. of page 4)

CAS No. / Designation of material / % / Type / Value / Unit	
<b>CAS: 1317-65-3 calcium carbonate</b>	
TWA (Italy)	Long-term value: 10 mg/m <sup>3</sup> (e)
<b>CAS: 65997-15-1 Cement, portland, chemicals</b>	
AGW (Germany)	Long-term value: 5 E mg/m <sup>3</sup> DFG
LEP (Spain)	Long-term value: 4 mg/m <sup>3</sup> fracción respirable: e, d
TWA (Italy)	Long-term value: 1 mg/m <sup>3</sup> (e, j), A4
VLE (Portugal)	Long-term value: 1 mg/m <sup>3</sup> Fração resp.;A4,função pulm.,sintomas resp.,asma
HTP (Finland)	Long-term value: 5* 1** mg/m <sup>3</sup> *hengittyvä pöly, **alveolijae

**Additional Occupational Exposure Limit Values for possible hazards during processing:**

Total inhalable dust: 10 mg/m<sup>3</sup> ; Respirable dust: 1 mg/m<sup>3</sup>

UK and Ireland: Total inhalable dust: 10 mg/m<sup>3</sup> ; Respirable dust: 4 mg/m<sup>3</sup>

**Additional information:**

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

**8.2 Exposure controls**

**Appropriate engineering controls** No further data; see section 7.

**Individual protection measures, such as personal protective equipment**

**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

**Respiratory protection:**

Short term filter device:

Filter P2.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

**Hand protection** Protective gloves.

**Material of gloves** Nitrile impregnated cotton gloves complying with the standard EN 374-1.

**Eye/face protection** Tightly sealed goggles

**Body protection:** Protective work clothing.

EUG

(Contd. on page 6)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 19.08.2025

Version number 1

Revision: 26.10.2022

Trade name: weberkol flex dynamik

(Contd. of page 5)

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

##### General Information

<b>Physical state</b>	Solid.
<b>Colour:</b>	According to product specification
<b>Odour:</b>	Odourless
<b>Odour threshold:</b>	Not determined.
<b>Melting point/freezing point:</b>	Undetermined.
<b>Boiling point or initial boiling point and boiling range</b>	2,000 °C (DIN, CAS: 65996-69-2 Slags, ferrous metal, blast furnace)
<b>Flammability</b>	Product is not flammable.
<b>Lower and upper explosion limit</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
<b>Flash point:</b>	Not applicable
<b>Auto-ignition temperature:</b>	470 °C (DIN 51794, Copolymer of acrylic acid ester + ethylene +vinylester +additives)
<b>Decomposition temperature:</b>	Not determined.
<b>pH</b>	Mixture reacts violently with water.
<b>Viscosity:</b>	
<b>Kinematic viscosity</b>	Not applicable.
<b>dynamic:</b>	Not applicable.
<b>Solubility</b>	
<b>Water:</b>	Hardens when in contact with water.
<b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
<b>Vapour pressure:</b>	Not applicable.
<b>Density and/or relative density</b>	
<b>Density:</b>	Not applicable.
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not applicable.
<b>Particle characteristics</b>	See section 3.

#### 9.2 Other information

<b>Appearance:</b>	
<b>Form:</b>	Powder
<b>Important information on protection of health and environment, and on safety.</b>	
<b>Ignition temperature:</b>	Product is not self-igniting.
<b>Explosive properties:</b>	Product does not present an explosion hazard.
<b>EU-VOC (g/L)</b>	
<b>Solids content:</b>	100.0 %
<b>Change in condition</b>	
<b>Softening point/range</b>	
<b>Oxidising properties</b>	Not determined.

(Contd. on page 7)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 19.08.2025

Version number 1

Revision: 26.10.2022

Trade name: weberkol flex dinamik

(Contd. of page 6)

**Evaporation rate** Not applicable.

**Information with regard to physical hazard classes**

<b>Explosives</b>	Void
<b>Flammable gases</b>	Void
<b>Aerosols</b>	Void
<b>Oxidising gases</b>	Void
<b>Gases under pressure</b>	Void
<b>Flammable liquids</b>	Void
<b>Flammable solids</b>	Void
<b>Self-reactive substances and mixtures</b>	Void
<b>Pyrophoric liquids</b>	Void
<b>Pyrophoric solids</b>	Void
<b>Self-heating substances and mixtures</b>	Void
<b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
<b>Oxidising liquids</b>	Void
<b>Oxidising solids</b>	Void
<b>Organic peroxides</b>	Void
<b>Corrosive to metals</b>	Void
<b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Not reactive under normal conditions of use

When mixed with water the product hardens forming a stable non-reactive mass.

**10.2 Chemical stability** Stable at recommended storage conditions

**Thermal decomposition / Conditions to be avoided:**

No decomposition if used according to specifications.

#### 10.3 Possibility of hazardous reactions

Reacts with acids

Reacts with light alloys in the presence of moisture to form hydrogen

#### 10.4 Conditions to avoid

Avoid water ingress/moisture during storage (the product will react with moisture and harden).

**10.5 Incompatible materials:** No further relevant information available.

**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 8)

EUG

**Safety Data Sheet**  
 according to Regulation (EC) No 1907/2006, Article 31, as amended  
 by Regulation (EU) 2020/878.

Printing date 19.08.2025

Version number 1

Revision: 26.10.2022

**Trade name: weberkol flex dinamik**

(Contd. of page 7)

**LD/LC50 values relevant for classification:**

Components		Type	Value	Species
<b>CAS: 1317-65-3 calcium carbonate</b>				
Oral	LD50		>2,000 mg/kg	(Rat)
Dermal	LD50		>2,000 mg/kg	(Rat)
<b>CAS: 65997-15-1 Cement, portland, chemicals</b>				
Dermal	LD50		>2,000 mg/kg	(Rabbit)
<b>CAS: 65996-69-2 Slags, ferrous metal, blast furnace</b>				
Oral	LD50		>2,000 mg/kg	(Rat)
Dermal	LD50		>4,000 mg/kg	(Rat)

**Primary irritant effect:**

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/irritation** Causes serious eye damage.

**Respiratory or skin sensitisation** May cause an allergic skin reaction.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure** May cause respiratory irritation.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**11.2 Information on other hazards**

**Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity:** Not classified as harmful to aquatic life

Type of test / Effective concentration / Method / Assessment	
<b>CAS: 1317-65-3 calcium carbonate</b>	
LC50/96h	>100 mg/l (Fish)
EC50/48h	>100 mg/l (aquatic invertebrates)
EC50/72h	>14 mg/l (aquatic algae and cyanobacteria)
<b>CAS: 65996-69-2 Slags, ferrous metal, blast furnace</b>	
LC50/96h	>100 mg/l (Fish)
LC0/96h	>100 mg/l (Fish)
EC50/48h	>100 mg/l (aquatic invertebrates)
EC50/72h	>90,000 mg/l (aquatic algae and cyanobacteria)
NOEC (72h)	50-100 mg/l (aquatic algae and cyanobacteria)
NOEC (21d)	1,563 mg/l (aquatic invertebrates)
EC 0/48h	>100 mg /l (aquatic invertebrates)

(Contd. on page 9)

**Safety Data Sheet**  
 according to Regulation (EC) No 1907/2006, Article 31, as amended  
 by Regulation (EU) 2020/878.

Printing date 19.08.2025

Version number 1

Revision: 26.10.2022

**Trade name: weberkol flex dinamik**

(Contd. of page 8)

**12.2 Persistence and degradability** No further relevant information available.

<b>Method</b>
<b>CAS: 1317-65-3 calcium carbonate</b>
Biod. (28 days) >90 %

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

**12.5 Results of PBT and vPvB assessment**

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**12.7 Other adverse effects**

**Remark:**

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

**Behaviour in sewage processing plants:**

<b>Type of test / Effective concentration / Method / Assessment</b>
<b>CAS: 1317-65-3 calcium carbonate</b>
EC 50 (3h) >1,000 mg/l (microorganisms)
<b>CAS: 65996-69-2 Slags, ferrous metal, blast furnace</b>
EC 50 (3h) >10,000 mg/l (microorganisms)

**Additional ecological information:**

**General notes:**

Do not allow product to reach ground water, water course or sewage system.  
 Must not reach sewage water or drainage ditch undiluted or unneutralised.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Recommendation**

Dispose of the product in accordance with national and local regulations.

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish.

Possible waste code 17 09 04.

<b>European waste catalogue</b>	
10 13 11	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10
10 13 14	waste concrete and concrete sludge
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP13	Sensitising

(Contd. on page 10)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 19.08.2025

Version number 1

Revision: 26.10.2022

Trade name: weberkol flex dinamik

(Contd. of page 9)

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

**Recommended cleaning agent:** Thoroughly shake out sacks.

### SECTION 14: Transport information

<b>14.1 UN number or ID number</b> ADR, IMDG, IATA	Void
<b>14.2 UN proper shipping name</b> ADR, IMDG, IATA	Void
<b>14.3 Transport hazard class(es)</b> ADR, ADN, IMDG, IATA Class	Void
<b>14.4 Packing group</b> ADR, IMDG, IATA	Void
<b>14.5 Environmental hazards:</b>	Not applicable.
<b>14.6 Special precautions for user</b>	Not applicable.
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
<b>UN "Model Regulation":</b>	Void

### SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

**Labelling according to Regulation (EC) No 1272/2008** cf. section 2

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**REGULATION (EU) 2017/852 on mercury (Annex I)**

None of the ingredients is listed.

**REGULATION (EU) 2019/1021 on persistent organic pollutants (POP)**

None of the ingredients is listed.

**REGULATION (EC) No 1907/2006 ANNEX XVII**

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII Entry no. 47 Chromium VI compounds)

Conditions of restriction: 47

(Contd. on page 11)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 19.08.2025

Version number 1

Revision: 26.10.2022

**Trade name: weberkol flex dinamik**

(Contd. of page 10)

**Regulation (EU) No 649/2012**

None of the ingredients is listed.

**DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

**REGULATION (EU) 2019/1148**

**Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

**Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

**Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

**REGULATION (EU) 2024/590 on substances that deplete the ozone layer**

None of the ingredients is listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

**Relevant phrases**

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.
- EUH203 Contains chromium (VI). May produce an allergic reaction.

**Classification according to Regulation (EC) No 1272/2008**

Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--	--

**Department issuing SDS:** Research and development

(Contd. on page 12)

**Safety Data Sheet**  
according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 19.08.2025

Version number 1

Revision: 26.10.2022

**Trade name: weberkol flex dinamik**

(Contd. of page 11)

**Contact:**

Bariş Yıldırım  
(Sertifika No: TÜV/11.216.01 - Geçerlilik tarihi 19.10.2028)

Necati Utku Erol  
(Sertifika No: TÜV/11.216.11 - Geçerlilik tarihi 19.10.2028)

Sesil Genç  
(Sertifika No: TÜV/11.216.13 - Geçerlilik tarihi 19.10.2028)

Cerem Pişkin  
(Sertifika No: TÜV/13.85.02 - Geçerlilik tarihi 12.10.2028)

**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

**\* Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.